



**Technical Characteristics**

|                          |  |
|--------------------------|--|
| Ampere Rating            | 5A   |
| Approvals                | UL Listed File: E42259 CCN NKGR - CSA Certified File: LR 25490 Class 3211 03 - CE Marked |
| Catalog Reference Number | 9001CT0001   |
| Contact Configuration    | 1 N.O./1 N.C.  |
| Enclosure Type           | For Hazardous Location Usage - Explosion Proof (Indoor)                                  |
| Enclosure Rating         | NEMA 7/9   |
| Markings                 | START/STOP   |
| Maximum Voltage Rating   | 600V   |
| Mounting Type            | Surface  |
| Number of Operators      | 2  |
| Operators                | (2) Momentary Pushbuttons (Lockout on STOP)  |
| Terminal Type            | Screw Clamp  |
| Type                     | B  |

**Shipping and Ordering**

|                   |   |
|-------------------|---|
| Category          | 21421 - Stations, Control, Standard duty, Type B                        |
| Discount Schedule | CP1   |
| Article Number    | 785901600886  |
| Package Quantity  | 1   |
| Weight            | 3.57 lbs.   |
| Availability Code | Stock Item: This item is normally stocked in our distribution facility. |
| Returnability     | Y   |

As standards, specifications, and designs change from time to time, please ask for confirmation of the information given in this document.