9001KXRD113

Dual Pushbutton , Non-Illuminated, (2) Momentary (with interlock), Type: KX

Technical Characteristics

| Bezel Material | Chromium Plated Metal |
|--------------------------|---|
| Button/Cap Color | Green-Green |
| Ampere Rating | 10A |
| Approvals | UL Listed File Number E42259 CCN NKCR - CSA Certified File Number LR25490 Class 3211 03 - CE Marked |
| Button Type | Standard |
| Catalog Reference Number | 9001CT0001 |
| Contact Configuration | 2 N.O./2 N.C. |
| Contact Material | Silver Alloy |
| Enclosure Type | Water tight, Dust tight, Oil tight and Corrosion Resistant (Indoor/Outdoor) |
| Enclosure Rating | NEMA 4/4X/13; IP65 |
| Head Type | Square |
| Markings | OPEN/CLOSE |
| Maximum Voltage Rating | 600V |
| Mounting Type | Panel |
| Mounting Position | All |
| Number of Operators | 2 |
| Operator Action | (2) Momentary (with interlock) |
| Operator Type | Non-Illuminated |
| Terminal Type | Screw Clamp |
| Size | 30mm |
| Utilization Category | AC15 - DC13 |
| Туре | KX |

Shipping and Ordering

| Category | 21427 - Push Buttons, 30 mm, Square, Type KX |
|-------------------|---|
| Discount Schedule | CP1 |
| Article Number | 785901786740 |
| Package Quantity | 1 |
| Weight | 0.3 lbs. |
| Availability Code | Non-Stock Item: This item is not normally stocked in our distribution facility. |
| Returnability | Y |

As standards, specifications, and designs change from time to time, please ask for confirmation of the information given in this document.

