

9001SK1L1GH13

Pushbutton , Illuminated, Momentary, Type: K,
Size: 30mm, 10A, 600V



Technical Characteristics

Ampere Rating	10A
Approvals	UL File Number E42259 CCN NKCR - CSA File Number LR24590 Class 3211-03 - CE Marked
Bezel Material	Black Plastic
Button/Cap Color	Green
Button Type	Standard Pushbutton
Guard Type	Full Guard (Clear Plastic)
Contact Configuration	1 NO - 1 NC
Contact Block Code	H13
Contact Type	Standard (Fingersafe)
Enclosure Type	Water tight, Dust tight, Oil tight and Corrosion Resistant (Indoor/Outdoor)
Enclosure Rating	NEMA 1/2/3/3R/4/4X/6/12/13
Head Type	Round
Light Module Supply Voltage	110/120VAC@50/60Hz
Light Module Type	Transformer
Maximum Voltage Rating	600V
Markings	None
Mounting Type	Panel
Number of Operators	1
Number of Positions	2
Operator Action	Momentary
Operator Type	Illuminated
Size	30mm
Terminal Type	Screw Clamp
Type	K
Utilization Category	AC15 - DC13

Shipping and Ordering

Category	21429 - Push Buttons, Corrosion Resistant, Type SK & SKY
Discount Schedule	CP1
GTIN	00785901040354
Package Quantity	1
Weight	0.46 lbs.
Availability Code	Stock Item: This item is normally stocked in our distribution facility.
Returnability	Y
Country of Origin	MX

Generated: 01/05/2010 15:13:45

As standards, specifications, and designs change from time to time, please ask for confirmation of the information given in this document.

Generated: 01/05/2010 15:13:45