9001SKR1UH6

Pushbutton , Non-Illuminated, Momentary, Type: SK, Size: 30mm, 10A, 600V

Technical Characteristics

| Bezel Material | Plastic |
|--------------------------|---|
| Button/Cap Color | Universal Set (1 of each: Black, Red, Green, Yellow, Orange, Blue and White) |
| Ampere Rating | 10A |
| Approvals | UL Listed File Number E42259 CCN NKCR - CSA Certified File Number LR25490 Class 3211 03 - CE Marked |
| Button Type | Standard |
| Guard Type | Full Guard |
| Catalog Reference Number | 9001CT0001 |
| Contact Configuration | 1 N.C. |
| Contact Material | Silver Alloy |
| Enclosure Type | Water tight, Dust tight, Oil tight and Corrosion Resistant (Indoor/Outdoor) |
| Enclosure Rating | NEMA 4/4X/13 |
| Head Type | Round |
| Maximum Voltage Rating | 600V |
| Mounting Type | Panel |
| Mounting Position | All |
| Number of Operators | 1 |
| Operator Action | Momentary |
| Operator Type | Non-Illuminated |
| Terminal Type | Screw Clamp |
| Туре | SK |
| Size | 30mm |
| Utilization Category | AC15 - DC13 |

Shipping and Ordering

| Category | 21429 - Push Buttons, Corrosion Resistant, Type SK & SKY |
|-------------------|---|
| Discount Schedule | CP1 |
| Article Number | 785901042136 |
| Package Quantity | 1 |
| Weight | 0.16 lbs. |
| Availability Code | Non-Stock Item: This item is not normally stocked in our distribution facility. |
| Returnability | Y |

As standards, specifications, and designs change from time to time, please ask for confirmation of the information given in this document.

