9001SKR4R05H13

Pushbutton, Non-Illuminated, Momentary, Type: SK, Size: 30mm, 10A, 600V

List Price \$86.00 USD

Availability Non-Stock Item: This item is not normally stocked in our distribution

Technical Characteristics

Bezel Material	Plastic
Button/Cap Color	Red
Ampere Rating	10A
Approvals	UL Listed File Number E42259 CCN NKCR - CSA Certified File Number LR25490 Class 3211 03 - CE Marked
Button Type	Snap-In Mushroom (1.38 Inch)
Guard Type	No Guard
Catalog Reference Number	9001CT0001
Contact Configuration	1 N.O./1 N.C.
Contact Material	Silver Alloy
Enclosure Type	Water tight, Dust tight, Oil tight and Corrosion Resistant (Indoor/Outdoor)
Enclosure Rating	NEMA 4/4X/13
Head Type	Round
Markings	EMERGENCY STOP
Maximum Voltage Rating	600V
Mounting Type	Panel
Mounting Position	All
Number of Operators	1
Operator Action	Momentary
Operator Type	Non-Illuminated
Terminal Type	Screw Clamp
Size	30mm
Туре	SK
Utilization Category	AC15 - DC13

Shipping and Ordering

Category	21429 - Push Buttons, Corrosion Resistant, Type SK & SKY
Discount Schedule	CP1
Article Number	785901042808
Package Quantity	1
Weight	0.5 lbs.
Availability Code	Non-Stock Item: This item is not normally stocked in our distribution facility.
Returnability	Υ

As standards, specifications, and designs change from time to time, please ask for confirmation of the information given in this document.





Generated: 06/08/2009 15:38:31