9001SKR9P1RH13

Pushbutton , Illuminated, Maintained (Push/Pull), Type: SK, Size: 30mm



List Price		
Availability		

Technical Characteristics

Toominour Gridiantionion	
Bezel Material	Plastic
Button/Cap Color	Red
Ampere Rating	10A
Approvals	UL Listed File Number E42259 CCN NKCR - CSA Certified File Number LR25490 Class 3211 03 - CE Marked
Button Type	Snap-In Mushroom (1.63 Inch)
Guard Type	Full Guard
Catalog Reference Number	9001CT0001
Contact Configuration	1 N.O./1 N.C.
Contact Material	Silver Alloy
Enclosure Type	Water tight, Dust tight, Oil tight and Corrosion Resistant (Indoor/Outdoor)
Enclosure Rating	NEMA 4/4X/13
Head Type	Round
Light Module Supply Voltage	110/120VAC@50/60Hz
Light Module Type	Transformer
Maximum Voltage Rating	600V
Mounting Type	Panel
Mounting Position	All
Number of Operators	1
Operator Action	Maintained (Push/Pull)
Operator Type	Illuminated
Terminal Type	Screw Clamp
Size	30mm
Туре	SK
Utilization Category	AC15 - DC13

Shipping and Ordering

Category	21429 - Push Buttons, Corrosion Resistant, Type SK & SKY	
Discount Schedule	CP1	
Article Number	785901043102	
Package Quantity	1	
Weight	0.47 lbs.	
Availability Code	Stock Item: This item is normally stocked in our distribution facility.	
Returnability	Υ	

Generated: 06/08/2009 16:28:39





Schneider