

**Technical Characteristics**

|                          |   |
|--------------------------|---|
| Bezel Material           | Plastic   |
| Ampere Rating            | 10A   |
| Approvals                | UL Listed File Number E42259 CCN NKCR - CSA Certified File Number LR25490 Class 3211 03 - CE Marked |
| Catalog Reference Number | 9001CT0001  |
| Contact Configuration    | 1 N.O./1 N.C.   |
| Contact Material         | Silver Alloy  |
| Enclosure Type           | Water tight, Dust tight and Oil tight (Indoor/Outdoor)  |
| Enclosure Rating         | NEMA 4/4X/13  |
| Head Type                | Round   |
| Cam Type                 | Cam C   |
| Knob Color               | Black   |
| Knob Type                | Standard  |
| Maximum Voltage Rating   | 600V  |
| Mounting Type            | Panel   |
| Mounting Position        | All   |
| Number of Operators      | 1   |
| Number of Positions      | 3   |
| Operator Action          | Maintained  |
| Operator Type            | Non-Illuminated   |
| Terminal Type            | Screw Clamp   |
| Size                     | 30mm  |
| Type                     | SK  |
| Utilization Category     | AC15 - DC13   |

**Shipping and Ordering**

|                   |   |
|-------------------|---|
| Category          | 21429 - Push Buttons, Corrosion Resistant, Type SK & SKY                |
| Discount Schedule | CP1   |
| Article Number    | 785901043720  |
| Package Quantity  | 1   |
| Weight            | 0.19 lbs.   |
| Availability Code | Stock Item: This item is normally stocked in our distribution facility. |
| Returnability     | Y   |

As standards, specifications, and designs change from time to time, please ask for confirmation of the information given in this document.