HDL26020

Molded Case Circuit Breaker , 600VAC/250VDC, 20A





by Schneider Electric

Technical Characteristics

Approvals	UL Listed - CSA Certified - IEC Rated
Catalog Reference Number	0611CT0401
Circuit Breaker Type	Standard
For Use With	Industrial Enclosures and Switchboards
General Application	Provides overload and short circuit protection
Marketing Trade Name	Powerpact
AC Magnetic Trip Setting	350A - 750A Adjustable Trip
Ampere Rating	20A
Frame Type	H-Frame
Voltage Rating	600VAC/250VDC
Mounting Type	Unit Mount
Weight	5 Pounds
Number of Poles	2-Pole
Short Circuit Current Rating	25kA@240VAC - 18kA@480VAC - 14kA@600VAC
Туре	HD
Terminal Type	Line: Lug - Load: Lug
Wire Size	#14-3/0 AWG(Al/Cu)
Height	6.40 Inches
Width	2.74 Inches
Depth	4.36 Inches

Shipping and Ordering

Category	01110 -
Discount Schedule	DE2
Article Number	785901577966
Package Quantity	1
Weight	3 lbs.
Availability Code	Non-Stock Item: This item is not normally stocked in our distribution facility.
Returnability	Υ

As standards, specifications, and designs change from time to time, please ask for confirmation of the information given in this document.

Generated: 06/01/2009 12:51:42

