



Technical Characteristics

| | |
|------------------------------|--|
| Approvals | UL Listed - CSA Certified - IEC Rated |
| Catalog Reference Number | 0611CT0401 |
| Circuit Breaker Type | Standard |
| For Use With | Industrial Enclosures and Switchboards |
| General Application | Provides overload and short circuit protection |
| AC Magnetic Trip Setting | 900A - 1700A Adjustable Trip |
| Ampere Rating | 125A |
| Frame Type | H-Frame |
| Marketing Trade Name | Powerpact |
| Voltage Rating | 600VAC/250VDC |
| Mounting Type | Unit Mount |
| Weight | 5 Pounds |
| Number of Poles | 2-Pole |
| Short Circuit Current Rating | 25kA@240VAC - 18kA@480VAC - 14kA@600VAC |
| Type | HD |
| Terminal Type | Line: Lug - Load: Lug |
| Wire Size | #14-3/0 AWG(Al/Cu) |
| Height | 6.40 Inches |
| Width | 2.74 Inches |
| Depth | 4.36 Inches |

Shipping and Ordering

| | |
|-------------------|---|
| Category | 01110 - |
| Discount Schedule | DE2 |
| Article Number | 785901461944 |
| Package Quantity | 1 |
| Weight | 3.06 lbs. |
| Availability Code | Non-Stock Item: This item is not normally stocked in our distribution facility. |
| Returnability | Y |

As standards, specifications, and designs change from time to time, please ask for confirmation of the information given in this document.