



**Technical Characteristics**

Approvals	UL Listed - CSA Certified - IEC Rated
Circuit Breaker Type	Standard
Catalog Reference Number	0611CT0401
For Use With	Industrial Enclosures and Switchboards
Ampere Rating	250A
General Application	Provides overload and short circuit protection
AC Magnetic Trip Setting	1250A - 2500A Adjustable Trip
Frame Type	J-Frame
HACR Rated	Yes
Marketing Trade Name	Powerpact
Voltage Rating	600VAC/250VDC
Mounting Type	Unit Mount
Number of Poles	2-Pole
Weight	5 Pounds
Short Circuit Current Rating	25kA@240VAC - 18kA@480VAC - 14kA@600VAC
Terminal Type	Line: Lug - Load: Lug
Type	JD
Wire Size	#3/0-350 AWG/kcmil(Al/Cu)
Height	7.52 Inches
Width	4.12 Inches
Depth	5.00 Inches

**Shipping and Ordering**

Category	01110 -
Discount Schedule	DE2
Article Number	785901839880
Package Quantity	1
Weight	4.65 lbs.
Availability Code	Non-Stock Item: This item is not normally stocked in our distribution facility.
Returnability	Y

As standards, specifications, and designs change from time to time, please ask for confirmation of the information given in this document.

Generated: 06/01/2009 12:21:32