



Technical Characteristics

| | |
|------------------------------|---|
| Application | Suitable for use in service entrance locations |
| Approvals | Listed to UL 1449 Second Edition and UL 1283 - Meets requirements of ANSI/IEEE C62.41 and C62.45 and UL Category Section 37.3 |
| Short Circuit Current Rating | 200kA |
| Wiring Configuration | 3 or 4-Wire |
| LED Indicator | Normal: Green - Fault: Red (for each phase) |
| Marketing Trade Name | Surgelogic |
| Catalog Reference Number | 1310CT0202 |
| Includes | Surge Counter and Audible alarm (with enable/disable switch) |
| Enclosure Rating | NEMA 3R/12 |
| Enclosure Material | Painted Steel |
| Mounting Type | Surface/Flush |
| Phase | 3-Phase |
| Service Voltage | 208Y/120VAC |
| Maximum Surge Current | 480kA/phase |
| Type | EMA |

Shipping and Ordering

| | |
|-------------------|---|
| Category | 08252 - Panelboards, |
| Discount Schedule | PE1A |
| Article Number | 785901653721 |
| Package Quantity | 1 |
| Weight | 54.3 lbs. |
| Availability Code | Non-Stock Item: This item is not normally stocked in our distribution facility. |
| Returnability | N |

As standards, specifications, and designs change from time to time, please ask for confirmation of the information given in this document.