

Switchcraft® ...U.S. Manufacturer of Industrial and Pro Audio/Broadcast Products Since 1946.

[Home](#)

[About Us](#)

[Products](#)

[Sales](#)

[Distributors](#)

[Search](#)

[Links](#)

[Contact Us](#)

PANEL MOUNT DC POWER JACKS



1. 712A
2. PC712A
3. 2C1072
4. L722A

FEATURES

*2 conductor jack.

*Automatic switch over from AC to DC permitted by sleeve shunt spring.

*Split center pin shaped to hold mating plug firmly. (732A available in solid center pin only.)

*Choose solder lug or PC terminal. (732A not available in PC terminal.)

*Bushing length available as .219" or extended .319 to permit use in thicker panels. (732A not available in extended length.)

*L712A and PCL712A accept plugs with .475" long, 0.099" diameter sleeve.

*L722A and PCL722A accept plugs with .475" long, 0.08" diameter sleeve.

MOUNTING

Part Numbers 712A, 722A and 732A - Mounts in .313 inch diameter hole in panels up to .125 inches thick (maximum).

Part Numbers PC712A and PC722A - Same as 712A. See drawing for PC board layout.

Part Number 2C1072 - Jack covers for 712A, 722A and 732A - special order only.

For insulated mounting, two insulated washers are available on special order. Mounting hole diameter is .375 inches. See "Insulated Mounting" drawing.

Part Number P2442 - Phenolic flat washer.

Part Number S4263 - Swedged fiber washer.

SPECIFICATIONS

MECHANICAL

Life: 10,000 insertion/withdrawal cycles minimum.

Insertion/Withdrawal Forces: 3 pound insertion (maximum), 4 ounce minimum withdrawal.

Part Numbers 712A, PC712A, 722A, PC722A, 732A

ELECTRICAL

Contact Resistance: .01 ohms maximum (initial), .02 ohms maximum (after humidity, durability exposure), .1 ohms maximum (after salt spray).

Insulation Resistance: 10,000 M(ohm) minimum (initial), 1,000 M(ohm) minimum (after humidity, durability exposure).

Dielectric Withstanding Voltage: 500 V AC maximum.

Contact Rating: 5 A, 12 V DC. resistive.

MATERIAL

Housing: Molded plastic.

Mounting Bushing and Hex Nut: Plated copper alloy.

Pin, Spring and Terminals: Plated copper alloy.

Insulators: Rigid plastic.

Hardware: Supplied with one **Number P2439** nickel-plated brass hex nut, and one **Number P2441** nickel-plated steel flat washer.

Part Number	Description	Outside Diameter*	Typical Mating Plug**
712A	Solder lugs	0.1 inches (.097-.099)	760
PC712A	PC terminals		760K
L712A	Longer Bushing		761K
722A	Solder lugs	0.08 inches (.075-.077)	S760
PC722A	PC terminals		S760K

L722A	Longer Bushing		S761K
732A	Solder lugs	0.05 inches	860

* Center pin diameter.

** Other mating Plugs are available.

[click here to download p.c. board layouts and dimensional drawings](#)
(you will need to have Adobe Acrobat installed on your system to do this)



To search a category please click on the corresponding button:

| [Connectors](#) | [Jacks and Plugs](#) |
| [Patch Panels, Patch Kits & Jackfields](#) | [Cable Assemblies and Patch Cords](#) | [Switches](#) |

All products shown are covered by Switchcraft's limited lifetime warranty.

Switchcraft Inc., 5555 N. Elston Ave., Chicago, IL 60630
Phone: 773-792-2700 Fax: 773-792-2129