

180W to 300W Industrial ATX Power Supplies



- ◆ 90 - 150W convection cooled ratings
- ◆ 1U high
- ◆ Power factor corrected
- ◆ Peak power ratings
- ◆ No minimum loading required

RoHS

Features and Benefits

Feature

- ◆ Convection cooled ratings
- ◆ Low profile
- ◆ Industrial grade
- ◆ No minimum loading

Benefit

- ◆ No forced air or fan needed
- ◆ Fits into 1U high enclosures
- ◆ Greater reliability and field life
- ◆ Easier to use

Specifications

| ITEMS | MODELS | ZWX180 | ZWX240 | ZWX300 |
|----------------------------------|--------|--|---------------------------------|--------------------|
| Input Voltage | V | | 85-265VAC (47-63Hz) | |
| Input Current (1)(2) | A | 1.9 / 1.0 | 2.6 / 1.3 | 3.2 / 1.6 |
| Inrush Current (2) | A | | 14 / 28 Cold start 25°C ambient | |
| Power Factor | - | | Meets EN61000-3-2 | |
| Leakage Current | mA | | < 0.75mA | |
| Temperature Coefficient | °C | | <0.02%/°C | |
| Overcurrent Protection (3) | - | >1.05% of forced air current rating (5s delay and manual reset on V1, 2 & 3) | | |
| Oversupply Protection (4) | V | +3.3V: 3.76 - 4.3V, +5V: 5.74 - 7V, +12V: 13.4 - 15.6V | | |
| Hold Up Time (Typ) | (1) ms | | 20ms at 100VAC | |
| Efficiency (1)(2) | % | | 81 / 84% | |
| Remote On/Off PS_ON | - | High: Unit off, Low: Unit On (enabled). Meets SFX 12V | | |
| DC Good PWR_OK | - | High: Power supply is good. Meets SFX12V | | |
| Remote Sense | - | | +3.3V Only | |
| Output Voltage Setpoint Accuracy | - | | ±5% (all outputs) | |
| Output Voltage Adjustment | - | | None | |
| Line Regulation | mV | 3.3V: 20mV, 5V: 48mV, +12V: 48mV, -12V: 20mV, +5Vsb: 20mV | | |
| Load Regulation | mV | 3.3V: 100mV, 5V: 300mV, +12V: 300mV, -12V: 100mV, +5Vsb: 100mV | | |
| Ripple & Noise | mV | 3.3V: 120mV, 5V: 150mV, +12V: 150mV, -12V: 120mV, +5Vsb: 120mV | | |
| Operating Temperature | - | -10°C to +70°C, derate linearly to 20% load from 50°C to 70°C | | |
| Storage Temperature | °C | | -30 to +85°C | |
| Humidity (non condensing) | - | Operating: 30 - 90%RH, Non operating: 10 - 95% RH | | |
| Cooling | - | Convection or forced air cooled (30CFM, 0.85m³/min) | | |
| Withstand Voltage | - | I/P to Grnd 2kVAC (20mA), I/P to O/P 3kVAC (20mA), O/P to Grnd 500VAC (100mA) for 1 min. | | |
| Isolation Resistance | - | >100M at 25°C & 70%RH, Output to Ground 500VDC | | |
| Vibration (non operating) | - | 10 - 55Hz (1 minute sweep), 19.6m/s² constant X, Y, Z 1 hour | | |
| Shock (non operating) | - | < 392m/s² | | |
| Safety Agency Approvals | - | UL60950-1, CSA60950-1, EN60950-1, EN50178 (OV II), CE Mark | | |
| Conducted & Radiated EMI | - | EN55011/EN55022-B, FCC Class B, VCCI-B | | |
| Immunity | - | EN61000-4-2, -3, -4, -5, -6, -8, -11 | | |
| Weight (Typ) | g | 500 | 650 | 800 |
| Size (WxHxD) | in | 3.7 x 1.42 x 8.27 | 4.17 x 1.42 x 8.86 | 4.65 x 1.42 x 9.84 |
| Warranty | yrs | | Three Years | |

(1) With output loading of:

ZWX180: V1=6.5A, V2=6.5A, V3=7.7A, V4=0.2A, V5=1A

ZWX240: V1=8.9A, V2=7.7A, V3=10.2A, V4=0.3A, V5=2A

ZWX300: V1=12A, V2=7A, V3=1=5A, V3-2=9.4A, V4=0.2A, V5=1A

(2) 100/200VAC

(3) Avoid prolonged operation in overload

(4) <5s operation at peak load

Output Ratings

| Model | Output Voltage | Max Curr. (Convection) | Max Power (Convection) | Max Curr. (Forced Air) | Max Power (Forced Air) | Peak Curr.(4) (Forced Air) | Peak Power(4) (Forced Air) |
|--------|----------------|------------------------|------------------------|------------------------|------------------------|----------------------------|----------------------------|
| ZWX180 | V1 +3.3V | 6A(5) | 90W | 8.4A(5) | 153W | 12A(5) | 180W |
| | V2 +5V | 5A(5) | | 7A(5) | | 10A(5) | |
| | V3 +12V | 6A | | 9A | | 13A | |
| | V4 -12V | 0.2A | | 0.3A | | - | |
| | V5 +5V (sb) | 1.4A | | 2A | | - | |
| ZWX240 | V1 +3.3V | 7A | 120W | 9.8A | 204W | 14A | 240W |
| | V2 +5V | 6A | | 8.4A | | 12A | |
| | V3 +12V | 8A | | 11.2A | | 16A | |
| | V4 -12V | 0.2A | | 0.3A | | - | |
| | V5 +5V (sb) | 1.4A | | 2A | | - | |
| ZWX300 | V1 +3.3V | 10A | 150W | 14A | 255W | 20A | 300W |
| | V2 +5V | 6A | | 8.4A | | 12A | |
| | V3-1 +12V | 4A(6) | | 5.6A | | 8A(7) | |
| | V3-2 +12V | 8A(6) | | 11.2A | | 16A(7) | |
| | V4 -12V | 0.2A | | 0.4A | | - | |
| | V5 +5V (sb) | 1.4A | | 2A | | - | |

(5) Maximum combined power of V1 & V2: 32W convection, 54W forced air, 63W peak

(6) V3-1 & V3-2 combined current limited to 10.9A (131W)

(7) V3-1 & V3-2 combined current limited to 22A (264W)

Cable Harness

| Connector | Harness | ZWX180 | ZWX240 | ZWX300 |
|-------------|-----------|--------|--------|--------|
| CN1 | HA-2-IN | Y | Y | Y |
| CN21 | ZWX-HA-04 | Y | Y | Y |
| CN21(S-ATA) | ZWX-HA-02 | Y | Y | Y |
| CN31/CN41 | ZWX-HA-01 | Y | Y | Y |
| CN51 | ZWX-HA-03 | - | - | Y |

Options

| Suffix | Description |
|--------|--|
| Blank | Open Frame |
| /L1 | L bracket - input on the left side (rear mounting side facing away) |
| /L2 | L bracket - input on the right side (rear mounting side facing away) |
| /A1 | L bracket & cover - input on the left side (rear mounting side facing away) |
| /A2 | L bracket & cover - input on the right side (rear mounting side facing away) |

Other Lambda Industrial Products

| | |
|-------------|--|
| ZWS, ZWSPAF | 5-480W Single Output, 115/230VAC input |
| NV | 175W to 300W 4-5 Outputs |

Outline Drawing (ZWX300)