

Handheld Accessories

THS700 Oscilloscope Probes • Battery Charger • Hardcase

Probes for the THS700 Series

Passive voltage probes standard with the THS700 Series.



THS7CHG TekScope® Battery Charger

- 12 to 18 volt input (DC)
- 2 hour charge time



THS7HCA Hard Carrying Case

- Holds TekScope oscilloscope and accessories

Product Information

[> Introduction](#)

[Ordering Information](#)

Pricing Information

[Check List Price](#)

[Request a Quote](#)

width=1

Additional Resources

[Find an Authorized Distributor](#)



THS7BAT NiCad Battery Pack

- 4.8 volt
- 2.8 A/hour



P6117 standard with the THS720A and THS730A.



P5102 standard with the THS720P.

Passive Voltage Probes

Probe	Cable Length	Bandwidth	Attenuation	Comp. Range	Input C	System Input resistance	Maximum input	Scopes
P6117 *1	2 m	200 MHz	10X	15 to 35 pF	13.3 pF	10.0 MΩ	300 V _{RMS} CAT II	720A/730A

P5102 *1	2 m	100 MHz	10X	24 to 28 pF	11.2 pF	5.0 MΩ	1,000 V _{RMS} Float to 600V CAT II	THS720P (only)
--------------------------	-----	---------	-----	-------------	---------	--------	---	----------------

*1 Both of these probes can be used with any of the THS700 Series Scopes. This only designates that these probes come standard with the scopes.



A621



A622

General Purpose Current Probes (Typical Specifications)

Model Number	Frequency Range	Current Range RMS to Peak	Max. Conductor	Termination
A621	5 Hz to 50 kHz	100 mA to 2,000 A	54 mm dia.	BNC
A622	DC to 100 kHz	50 mA to 100 A	11.8 mm dia.	BNC

[▲ back to top](#)

[> Introduction](#)

[Ordering Information](#)

[Check List Price](#)

[Request a Quote](#)

width=1

[Find an Authorized Distributor](#)



Product(s) are manufactured in ISO registered facilities.

49W-15242-0C, 18-JUN-2005

