Product Data Sheet

ATSU01N212LT

Soft Start , 12A, 3HP@230VAC - 7.5HP@460VAC, Altistart 01, Type: ATS01



Technical Characteristics

| Ampere Rating | 12A |
|--------------------------|------------------------------|
| Degree of Protection | IP20 |
| External Control Voltage | 24VDC |
| Horsepower Rating | 3HP@230VAC - 7.5HP@460VAC |
| Input Voltage | 200-480VAC |
| Туре | ATS01 |
| Soft Starting Time | 1 to 10 seconds (adjustable) |
| Soft Stopping Time | 1 to 10 seconds (adjustable) |
| Depth | 5.31 inches |
| Marketing Trade Name | Altistart 01 |
| Number of Functions | 1 |
| Input Phase | 3-Phase |
| Height | 4.88 inches |
| Width | 1.77 inches |
| Output Phase | 3-Phase |
| | |

Shipping and Ordering

| Category | 22392 - |
|-------------------|---|
| Discount Schedule | 111 |
| Article Number | 785901760290 |
| Package Quantity | 1 |
| Weight | 0.97 lbs. |
| Availability Code | Non-Stock Item: This item is not normally stocked in our distribution facility. |
| Returnability | Ν |

As standards, specifications, and designs change from time to time, please ask for confirmation of the information given in this document.

