

NLC-MOD-USB

Order No.: 2701195



<http://eshop.phoenixcontact.de/phoenix/treeViewClick.do?UID=2701195>

Serial connection to PC's USB port for data transfer or software configuration

Commercial data	
EAN	4046356325400
Pack	1 pcs.
Customs tariff	85366990
Weight/Piece	0.0398 KG
Catalog page information	Page 261 (NTK-2008)

Product notes

WEEE/RoHS-compliant since:
10/15/2008



<http://www.download.phoenixcontact.com>
Please note that the data given here has been taken from the online catalog. For comprehensive information and data, please refer to the user documentation. The General Terms and Conditions of Use apply to Internet downloads.

Product description

Slot 1 option module. Connects the nanoLine controller to a Type A USB port. Functions as a serial device and requires special driver included on nanoNavigator CD.

Technical data

Interfaces

Interface	USB
-----------	-----

Type of connection	USB Type B
Transmission length	2 m

Supply

Supply voltage	24 V DC (Power available via base unit)
Max. current consumption	18 mA
Typical current consumption	10 mA

General data

Width	24.5 mm
Height	25.5 mm
Depth	49 mm
Degree of protection	IP20
Ambient temperature (operation)	-25 °C ... 60 °C
Ambient temperature (storage/transport)	-25 °C ... 85 °C

Accessories

Item	Designation	Description
General		
2701289	NLC-MOD-CAP	Replacement cover for slot 1 in base unit.
2701247	NLC-PC/USB-CBL 2M	Cable , serial

Address

PHOENIX CONTACT Inc., USA
586 Fulling Mill Road
Middletown, PA 17057, USA
Phone (800) 888-7388
Fax (717) 944-1625
<http://www.phoenixcon.com>



© 2009 Phoenix Contact
Technical modifications reserved;