LC1D32BL CONTACTOR 575VAC 32AMP IEC +OPTIONS

Technical Characteristics

Inductive Amperes (AC3)	32A
. , ,	
Contactor Type	Non-Reversing
Resistive Amperes (AC1)	50A
Certifications	UL Listed (E164862 / NLDX) - CSA Certified (LR43364 3211 04) - IEC Rated (60647-4) - CE Marked - RoHS Compliant
Horsepower Rating (3-Phase)	10HP@200/230Vac - 20HP@460Vac - 30HP@575Vac
Maximum Voltage Rating	600 Vac
Mounting Style	35mm DIN Rail
Marketing Trade Name	TeSys
Coil Voltage	24Vdc (Low Consumption)
Horsepower Rating (1-Phase)	2HP@115Vac - 5HP@230Vac
Number of Poles	3-Pole (3 NO)
Coil Voltage Code	BL
Coil Consumption Sealed	2.4 W
Coil Consumption Inrush	2.4 W
Control Wire Size	#10 to #18 AWG
Terminal Type	Screw Clamp
Weight	0.83 lbs (0.375 kg)
Control Terminal Torque	15 lb-in (1.7 Nm)
Power Terminal Torque	20 lb-in (2.5 Nm)
Power Wire Size	#6 to #14 AWG
Туре	TeSys D

Shipping and Ordering

Category	22345 -
Discount Schedule	l12
GTIN	00785901549512
Package Quantity	1
Weight	1.32 lbs.
Availability Code	Stock Item: This item is normally stocked in our distribution facility.
Returnability	Υ
Country of Origin	MX

As standards, specifications, and designs change from time to time, please ask for confirmation of the information given in this document.

Generated: 10/14/2009 11:16:41

