



*Generic photo of the product*

### Main technical characteristics of this part number

Family	<i>XCK-L</i>
Type of head	<i>Roller plunger</i>
Operator head	<i>Plunger</i>
Operating head	<i>With steel roller plunger</i>
Head control device (continued)	-
Action of angular movement	-
Operator	<i>By cam 30°</i>
Speed of attack max	<i>0.5m/s</i>
Min torque	<i>12 N</i>
Connection	<i>Screw clamps</i>
Output display	<i>Without</i>
Material - case	<i>Metal</i>
Dimensions of body (mm)	<i>52 x 72 x 30</i>
Mounting method	<i>Body</i>
Type of body	<i>Fixed</i>
Cable entry	<i>Gland incorporated</i>
Contact to operate	<i>Snap action</i>
Positive complete product	<i>Yes</i>
Contact unit	<i>N/O+N/C</i>
Form of contact	<i>Zb</i>
No. of steps	<i>1</i>
Mechanical conformity	-
Degree of protection	<i>IP66</i>
Temperature of operation	<i>-25...+70°C</i>

### Generic description of the product

Osiswitch Classic XCKM-XCKL-XCKML limit switch

Metal products

dimensions 63x64x30 or 52x72x30 or 81x77x30

heavy duty 15 to 20 million operations

enhanced tightness IP66.