Push Buttons and Operator Interface

XVB Illuminated Beacons and Indicating Banks Accessories

Support tube

Accessories Common to Beacon and Indicating Banks

Description

Support tube concealment cover

Mounting tulip with gasket

Incandescent bulbs bayonet type BA 15d, 10 W

Incandescent bulbs bayonet type BA 15d, 7 W

LEDs bayonet type BA 15d (sold singly)

Wall mount bracket



www.SquareD.com For the most up-to-date information

Catalog Number

XVBC02

XVBC03

XVBC04

XVBC020

XVBC030

XVBC040 XVBC11

XVBC12

DL1BLJ

DL1BLB

DL1BLE

DL1BLG

DL1BLM

DL1BEJ

DL1BEB

DL1BEE

DL1BEG

DL1BEM

DL1BDB1

DL1BDB3

DL1BDB4

DL1BDB6

DL1BDB8

DL1BDG1

DL1BDG3

DL1BDG4

DL1BDG6

DL1BDG8

XVBC14 XVBC00

XVBC02



XVBC020





Accessories Specific to Indicating Banks

| Description | Characteristics | Catalog Number | |
|---|---|----------------|--|
| Set of colored markers | 6 colors | XVBC22 | |
| Set of 5 legend holders | Identification of stacked units on base | XVBC23 | |
| Sheet of 85 legends for legend holder (XVBC23) | Identification of stacked units on base | XVBCY1 | |
| Sheet of 52 legends | Identification of stacked units on locking ring | XVBCY2 | |

With CM12 (pg 13.5) cable gland, for cable size of 0.4 to 0.55 in. (10 to 14 mm) diameter

1/2" NPT (for customer supplied tubing)

Characteristics

mm

100

400 800

100

400

800

White

Green

Red

Blue

Yellow-orange White

Green

Red

Blue

Yellow-orange

IN

3.94

15.75

31.50 3.94

15.75

31.50

12 Vac/dc

24 Vac/dc

48 Vac/dc

120 Vac/dc

230 Vac/dc

12 Vac/dc

24 Vac/dc

48 Vac/dc

120 Vac/dc

230 Vac/dc

24 Vac/dc

120 Vac


For mounting on tube XVBC0•


For direct mounting on base unit or with tulip XVBC11 + tube XVBC0•

Wiring Diagrams, Base Units

Screw terminals Torque to 4.4 in-lb (0.5 N•m)

XVBC12






For additional information, reference Catalog #9001CT0001.







XVA