



Illuminated Lens Units with Steady Light (2.75 in./70 mm diameter)

Description	Light Source and Voltage	Color	Catalog Number	
Illuminated lens unit	Bulb (10 W max) not included 250 Vac/dc max	Green	XVCB33	
		Red	XVCB34	
		Orange	XVCB35	
		Blue	XVCB36	
		Clear	XVCB37	
		Yellow	XVCB38	



Illuminated Lens Unit with Flashing Light (2.75 in./70 mm diameter)

Description	Light Source and Voltage	Color	Catalog Number			
Illuminated lens unit	Bulb (10 W max) not included 24 Vac 24–48 Vdc	Green	XVCB4B3			
		Red	XVCB4B4			
		Orange	XVCB4B5			
		Blue	XVCB4B6			
		Clear	XVCB4B7			
		Yellow	XVCB4B8			
		Bulb (10 W max) not included 48–230 Vac	Green		XVCB4M3	
			Red		XVCB4M4	
	Orange		XVCB4M5			
	Blue		XVCB4M6			
	Clear		XVCB4M7			
	Yellow		XVCB4M8			

For bulbs, see page 17-110.



Illuminated Lens Units with 10 Joule Strobe (2.75 in./70 mm diameter)

Description	Light Source and Voltage	Color	Catalog Number ▲			
Illuminated lens units	Strobe 24 Vac/dc	Green	XVCB8B3			
		Red	XVCB8B4			
		Orange	XVCB8B5			
		Blue	XVCB8B6			
		Clear	XVCB8B7			
		Yellow	XVCB8B8			
		Strobe 120 Vac	Green		XVCB8G3	
			Red		XVCB8G4	
	Orange		XVCB8G5			
	Blue		XVCB8G6			
	Clear		XVCB8G7			
	Yellow		XVCB8G8			
	Strobe 230 Vac	Green	XVCB8M3			
		Red	XVCB8M4			
		Orange	XVCB8M5			
		Blue	XVCB8M6			
		Clear	XVCB8M7			
		Yellow	XVCB8M8			

▲ For 5 Joule units, specify XVCB6**, instead of XVCB8** (\$155.00).

Note: There are no replacement lenses units for the XVCB strobe.



Audible Sounder Units (2.75 in./70 mm diameter)

Description	Supply Voltage	Catalog Number	
Sounder unit 90 dB at 1 m Adjustable from 75–90 dB Continuous or intermittent modes	12–48 Vac/dc	XVCB9B	
	120–230 Vac	XVCB9M	



Base Units + Cover (for direct or tube mounting, 2.75 in./70 mm diameter)

Description	For use with	Type	Catalog Number	
Base unit + cover for bottom or side cable entry	Banks	Standard	XVCB21	



For additional information, reference Catalog #9001CT0001.