

T&B® Fittings




T&B Catalog Number: 4920
UPC Number: 78621004920
Description: 1/2" Ranger; Liquidtight Cord Connector-45; . Body material-Malleable Iron; Gland nut and Grip Material-Steel; Bushing-Rubber. Cord range-.125-.375
Status: Active

Features

- Extended range with superior strain relief.
- Reduced overall size, fits into tighter spaces.
- Gland nut designed to restrict cable bending.

Application

Provide a means for passing a cord cable into an enclosure through a bulkhead; Form a mechanical grip and water and/or oil-resistant seal for cord; Form a non-slip connection or termination for flexible cord and cable.



General

Material Malleable Iron
Cord and Cable Types S, SO, SV, ST, STD, SJ, SJO, SJT, SJTO, SVD

Dimension Information

Hub Size (inches) 1/2
Dimension A (inches) 1 1/8
Dimension B (inches) 1 5/16
Dimension C (inches) 9/16
Cord Range (inches) .125-.375
Throat Diameter (inches) 37/64

Packaging

T&B Inner Pack 25
Package in Units 50
T&B Sold in UOM Each
T&B Weight Per UOM 18.6 lbs. per 100

Application Support

Product Overview Available on Website
Specifications Available on Website
Liquidtight Flexible Cord and Cable Connectors-Application and Features Available on Website
Portable Cord Selection Table Available on Website

Notes

***Note** Suitable for use in hazardous locations where general purpose equipment is specifically permitted by NEC 501-4(b).
****Note** Suitable for Ordinary, Wet or Dry locations.

Certifications

RoHS Compliance Yes

Certifications



File Nbr:
E 13938

Flexible Cords and Cable Fittings

The Ranger® Series of Steel Liquidtight Cord Connectors

The Ranger Series Steel Liquidtight Connector takes twice the cable range of most ordinary strain relief connectors. T&B's Ranger Connectors enable you to reduce your inventory and save time with one connector that can do the work of two.



Application

- Provide means for passing a cord cable into an enclosure, through a bulkhead or into a rigid conduit
- Form a mechanical grip and water and/or oil-resistant seal for cord
- Form a non-slip connection or termination for flexible cord

Cord & Cable Type

- S, SO, SV, ST, STD, SJ, SJO, SJT, SJTO, SVD

Features

- Extended range with superior strain relief
- Reduced overall size, fits into tighter spaces
- Gland nut designed to restrict cable bending

Materials

Body: Steel-2920 series, Malleable Iron-4920 & 4960 series
Gland Nut, Grip: Steel-all series
Bushing: Rubber

Environment Classification


- Ordinary locations
- Wet or dry locations

Range

Cord Range: .125" to .950"


Hub Size Range: 1/8" to 1"

Steel Liquidtight Strain Relief Connectors — Straight



CAT. NO.	HUB SIZE	THROAT DIA.	CORD RANGE	DIMENSIONS (IN.)		
				A	B	C
2920	1/8"	1/8"	.125-.375	1X	1X	X
2921	1/8"	1/8"	.310-.560	1X	1X	X
2922	1/8"	1/8"	.500-.750	1X	1X	X
2930	3/8"	1/8"	.125-.375	1X	1 1/2"	X
2931	3/8"	1/8"	.310-.560	1X	1 1/2"	X
2932	3/8"	1/8"	.500-.750	1X	1 1/2"	X
2940	1"	1/8"	.310-.560	1X	1X	1X
2941	1"	1/8"	.500-.750	1X	1X	1X
2942	1"	1/8"	.700-.950	1X	1X	1X

Steel Liquidtight Strain Relief Connectors — 90° Angle




CAT. NO.	HUB SIZE	THROAT DIA.	CORD RANGE	DIMENSIONS (IN.)		
				A	B	C
4960	1/8"	1/8"	.125-.375	1X	1X	X
4961	1/8"	1/8"	.310-.560	1X	1X	X
4962	1/8"	1/8"	.500-.750	1X	1 1/2"	X
4970	3/8"	1/8"	.125-.375	1X	1 1/2"	1 1/2"
4971	3/8"	1/8"	.310-.560	1X	1 1/2"	1 1/2"
4972	3/8"	1/8"	.500-.750	1X	1 1/2"	1 1/2"
4980	1"	1"	.310-.560	1X	2 1/2"	1 1/2"

All items shown on this page are suitable for use in hazardous locations where general purpose equipment is specifically provided by the NEC, NEC 501-40A.

U.L. File No. E-13938 CSA File No. 52391

Steel Liquidtight Strain Relief Connectors — 45° Angle



CAT. NO.	HUB SIZE	THROAT DIA.	CORD RANGE	DIMENSIONS (IN.)		
				A	B	C
4920	1/8"	1/8"	.125-.375	1X	1 1/2"	1 1/2"
4921	1/8"	1/8"	.310-.560	1X	1 1/2"	1 1/2"
4922	1/8"	1/8"	.500-.750	1X	1 1/2"	1 1/2"
4930	3/8"	1/8"	.125-.375	1X	1 1/2"	X
4931	3/8"	1/8"	.310-.560	1X	1 1/2"	X
4932	3/8"	1/8"	.500-.750	1X	1 1/2"	X
4940	1"	1/8"	.310-.560	1X	1 1/2"	1 1/2"

For wire mesh grips refer to pages A-111 & A-141.