

Catamount*

T&B Catalog Number: 90457IUV UPC Number: 72849412558

Description: 200 4" 100 5" 200 7" BLACK

Status: Active

Packaging	
Package in Units:	1
T&B Sold in UM:	EACH
T&B Weight per UOM:	1.16 lbs. per Each
General Information	
Country of Origin:	UNITED STATES
Harmonized Code:	3926909980
Certifications	
UL File Number(s):	66683

Catamount® Cable Ties

Catamount® Cable Tie Assortment Packages

- Natural nylon or black weather-resistant nylon
- Reusable jar
- · Easily merchandised
- · Great value
- Two size combinations and quantities





90650 and 90650-IUV

Cable Tie Assortments — Natural Nylon



CAT. NO.	CONTENTS	QTY.	BAGS/CASE	
CAT-711	L-7-50-9-C	100	25	
	L-11-50-9-C	50		
CAT-4811	L-4-18-9-C	100	35	
	L-8-40-9-C	100		
	L-11-50-9-C	50		
CAT-5811	L-5-30-9-C	200	35	
	L-8-40-9-C	200		
	L-11-50-9-C	50		

For UV Black assortments, add -B to Catalog Number.

Cable Tie Jar

CAT. NO.	LENGTH (IN.)	WIDTH	MAX, BUNDLE (IN.)	TENSILE STRENGTH	MATERIAL	JAR QTY.
90457-1	4	.100	X (.625)	18#		200
	5.6	.130	13 (1.25)	30#	Natural Nylon	100
	7.5	.187	18 (1.75)	50#		200
90457-IUV	4	.100	N (.625)	18#	Black Weather-	200
	5.6	.130	13 (1.25)	30#	Resistant.	100
	7.5	.187	18 (1.75)	50#	Nylon	200
90650-1	4	.100	N (.625)	18#		300
	7.5	.187	18 (1.75)	50#	Natural Nylon	300
	11.1	.187	3	50#		50
90650-IUV	4	.100	N (.625)	18#	Black Weather-	300
	7.5	.187	18 (1.75)	50#	Resistant.	300
	11.1	.187	3	50₩	Nylon	50

Cable Tie Mounting Bases

- %" and 1%" mounts for use with 18# through 50# tensile cable ties
- Supplied on rubber-based or acrylic closed cell foam adhesive or with no adhesive for #6 screw mount applications
- Available in 6.6 Natural Nylon and 6.6 Black Nylon
- UL* Flammability 94 V-2 (clip)



		./4
Cat. No.	MOUNT METHOD	COLOR
½™ Class		
MPNY-750-9-C	Synthetic Rubber Adhesive	Natural
MPNY-750-0-C	Synthetic Rubber Adhesive	Black
MPNY-750A-9-C	Acrylic Adhesive	Natural
MPNY-750A-0-C	Acrylic Adhesive	Black
MPWY-750S-9-C	#6 Screw	Natural
MPNY-750S-0-C 1" Class	#6 Screw	Black
MPNY-1000-9-C	Synthetic Rubber Adhesive	Natural Nylon
MPWY-1000-0-C	Synthetic Rubber Adhesive	Black Nylen
MPWY-1000A-9-C	Acrylic Adhesive	Natural Nylon
MPWY-1000A-0-C	Acrylic Adhesive	Black Nylen
MPWY-1000S-9-C	#6 Screw	Natural Nylon
MPNY-1000S-0-C	#6 Screw	Black Nylen

For use with 18-50 lb. Cable Ties

- Mounting Surface should be aleaned with alcohol based (PV) alcohol based (PV)
- Acrylic Based may be repositioned initially. Allow 24–72 hours setup for maximum performance with Acrylic Based adhesives
- For Rubber Based, allow 15 minutes setup for consistum performance