



Blackburn°

T&B Catalog Number: 9HPS

UPC Number: 78378620040

Description: Type HPS Plated Split-Bolt Connector with

Spacer made of Copper Alloy for Use on Copper, Aluminum, ACSR Conductors. Conductor Range for Equal Main and Tap

10 Str.-12 Sol.

Status: Active

Conductor Range Min. Tap with one Max. 12 Sol.

Features	
	Bolt and pressure bar of copper alloy, completely tin
	plated for corrosion resistance. Contoured spacer of
	electrolytic copper.

	, , , ,		
General			
Style	Type HPS		
Wire Type	Copper, Aluminum, ACSR		
Material	Copper Alloy		
Plating	Electro Tin-Plated		
Conductor Range for Equal Main and Tap 10 Str12 Sol.			

Dimension Information	
A (inches)	3/8
B (inches)	0.146
C (inches)	1/2
D (inches)	29/32
Packaging	
T&B Inner Pack	100
Package in Units	1000
T&B Sold in UOM	Each
T&B Weight Per UOM	2.83 lbs. per 100
Application Support	
T&B Sales Drawings	wsd-000072

	• •	
T&B Sales	Drawings	wsd-000072

Notes

Most connectors are UL and CSA Certified for cop-

per conductor only.

Blackburn Contax recommended when used on aluminum conductor.

Certifications

RoHS Compliance Yes

Certifications





File Nbr: E9809

For further technical assistance, please contact us...

T&B Technical Support MS 3B-50 8155 T&B Blvd. Memphis, TN 38125



U.S. Electrical On-line Catalog

Email:techsupport@tnb.com