





•	ker Label for Wire Range 2- Yellow Polyolefin, 3/4 inch,
---	---

Active

Status:

Images	
Image_1_s7	ezyhs14_ez1
Features	62y11314_621
	Perfect for wire and cable. Print heat-shrink sleeves on the spot.
	Clear, non smudging lettering. Chemical/solvent resistant. Available in yellow, white, and metallic markers.
	Flame retardant Polyolefin material, 3:1 shrink ratio. Easy to peel, split-back design.
General	
Style	Labels
Color	Yellow
Wire Range	2-4
Dimension Information	
Length (feet)	5
Width (inches)	3/4
Packaging	
T&B Inner Pack	1
Package in Units	5
T&B Sold in UOM	Each
T&B Weight Per UOM	12.6 lbs. per 100
Application Support	
Overview	Available on Website
Notes	
	Order in multiples of 5 cassettes.
	Labels fit EZL-100 only.
Certifications	
RoHS Compliance	Yes

## E-Z-Code°

# EZL-75 Thermal Label Printer and EZL Printer Labels

### Quick and cost-effective labeling solution!

#### EZL-75 Thermal Label Printer

If your labeling needs don't quite justify all the high-end features of T&B's EZL-100, now there's a lower cost solution for simple labeling. The EZL-75 thermal label printer is just as easy to use as the EZL-100. Simply type and print. Or don't even bother typing. Instead, use hot keys to choose among the EZL-75's built-in library of symbols and more than 150 commonly used words for security, location and voice/data/video labeling.



- Hot keys provide one-touch flagging for wires and cables and fixed-length labels for faceplates and security panels
- Incremental alpha and numeric printing makes printing distribution panel labels fast and simple
- 13-character backlit display enhances readability
- Multiple line printing supports up to 2 lines per label
- Durable bumper safeguards against damage in the tool box
- Uses the same label cassettes (up to ½" width) as EZL-100
  - ..... Specifications
- Dimensions: 4.5" (114mm) W x 7.5" (191mm) H x 2.1" (53mm) D
- Weight: 0.8 lbs. (363 grams)

 Power: 9V DC, using 6 "AA" (not included)batteries or AC adapter

included]batteries or AC ad

CAT. NO.	DESCRIPTION
EZL-75	Printer (includes (1) ½" white nylon quick-load cassette tape, quick start card, and user manual. AC power adapter not included
EZL-ADP	Adapter for EZ75 Printer 9% 1.5A

Surface Applications		Vinyl and Flex Nylon	Perm. Polyester	Heat Shrink
Wire	9	•		•
Cable	0	•		•
Curred	$\sim$	•		
Smooth		•	•	
Flat		•	•	
Textured	$\sim$	•	•	
Highly Textured	$\sim$	•		
Length	H	11.5	18.0'	5.0*
Width	I	方", 方" "元"	34°, 55° 34°	54°, 57° 56°, 57°

#### High-performance labels that last!

#### Wire Marker Labels for EZL Printers

- Perfect for wire and cable
- Print heat-shrink sleeves on the spot!
- Clear, non-smudging lettering
- Chemical/solvent resistant
- Available in yellow, white, and metallic markers
- Flame retardant, Polyolefin material, 3:1 shrink ratio
- · Easy-to-peel, split-back design



Easy barcode printing!

CAT. NO.	LABEL SIZE (IN.)	RECOMMENDED WIRE SIZE (AWG)	LENGTH
Clear Polyester			
EZ-CP12	M*	Flat Applications Only	18'
EZ-CP34	34 <b>"</b>	Flat Applications Only	18'
Red Vinyl			
EZ-RV34	¥.	Any	18'
White Permanent Polyester			
EZ-WP38	3°	Flat Applications Only	18'
EZ-WP12	M.	Flat Applications Only	18'
EZ-WP34*	¥"	Flat Applications Only	18'
Metallic Permanent Polyester			
EZ-MP38	3°	Flat Applications Only	18'
EZ-MP12	X*	Flat Applications Only	18'
EZ-MP34	¥.	Flat Applications Only	18'
White Flexible Nylon			
EZ-WW12	X*	Any	12.5
EZ-WN34*	3°	Any	12.5'
Yellow Flexible Nylon			
EZ-YN12	X*	Any	12.5
EZ-YN34*	5°	Any	12.5'
Heat-Shrink White Polyolefin La	ibels		
EZ-WHS14	X*	10 - 16	5'
EZ-WHS38	35	6-14	5'
EZ-WHS12	X*	4-6	5'
EZ-WHS34	3*	2 - 4	5'
Heat-Shrink Yellow Polyolefin L	abels		
EZ-YHS14	8.	10-16	5
EZ-YHS38	3*	6-14	5'
EZ-YHS12	X*	4-6	5'
EZ-YHS34	3*	2-4	5'
Order in multiples of 5 cassettes. * Labela Rt EZ2-100 only:			

E-Z-Code