



Ty-Rap®

T&B Catalog Number: LS-4.6-520A
UPC Number: 78621024217
Description: Cable Tie 302/304 Stainless Steel 100lb
 21" Ball Lock

Status: Active

General	
T&B Replacement Catalog Number	YLS4.6-520A
Material	304 Stainless Steel
Color	Metallic Gray
Dimension Information	
Length (inches)	20.5
Width (inches)	.180
Max. Wire Bundle Diameter (inches)	6
Specifications	
Tensile Strength (lbs.)	100
Temperature Rating	-112°F to 1000°F
Tooling	
Application Tools	DAS-250
Packaging	
T&B Order Multiple	100
T&B Inner Pack	100
Package in Units	5000
Package Type	Regular
T&B Sold in UOM	Each
T&B Weight Per UOM	1.23 lbs. per 100
Application Support	
Overview	Available on Website
Material Selection Guide	Available on Website



DAS-250
Preset tension tool
Automatic cut-off
Spare Blades Part No. BL 250 S

Stainless Steel Ties with Ball Locking Mechanism

Thomas and Betts introduces a range of self-locking, one-piece stainless steel ties, suitable for indoor or outdoor use.

Wide range of sizes

Six standard lengths up to 41" long will cover most applications with custom lengths available. Two widths are offered with minimum loop tensile strengths of 100 and 250 lbs. Space requirements are minimized by the low head profile – 20" maximum.

Fast, Easy Installation

Thomas & Betts stainless steel ties are self-locking, requiring no time consuming crimping or folding operations. The strong locking mechanism, incorporating a steel ball, requires a low insertion force while the strap section has rounded edges and smooth surfaces making the ties ideal for fast, safe, hand installation.

Two Materials

Two grades of stainless steel are available – 302/304 for standard applications and 316 for extra corrosion resistance. 302/304 and 316 stainless steels are non-magnetic and are ideal for high temperature applications ranging –80 °C to 538 °C.

Applications

- High temperature locations
- Marine environment (shipbuilding, salt water environment)
- Harsh environment (oil rigs, wash-down areas, refineries, food processing plants, auto car washers)
- Automotive plants

Ordering Information

Cat. No.	Length		Width		Max. Bundle Dia.		Tensile		Qty./box pcs.
	in.	mm.	in.	mm.	in.	mm.	lbs.	kg.	
302/304 Grade Stainless Steel									
LS-4.6-200A	7.9	201.0	0.18	4.6	2	51	100	45.3	100
LS-4.6-360A	14.2	360.0	0.18	4.6	4	102	100	45.3	100
LS-4.6-520A	20.5	520.0	0.18	4.6	6	152	100	45.3	100
LS-4.6-680A	26.7	679.0	0.18	4.6	8	203	100	45.3	100
LS-4.6-840A	33.0	838.0	0.18	4.6	10	254	100	45.3	100
LS-7.9-200A	7.9	201.0	0.31	7.9	3	51	250	113.3	50
LS-7.9-360A	14.2	360.0	0.31	7.9	4	102	250	113.3	50
LS-7.9-520A	20.5	520.0	0.31	7.9	6	152	250	113.3	50
LS-7.9-680A	26.7	679.0	0.31	7.9	8	203	250	113.3	50
LS-7.9-840A	33.0	838.0	0.31	7.9	10	254	250	113.3	50
LS-7.9-1010A	41.3	1050.0	0.31	7.9	12.5	318	250	113.3	50
316 Grade Stainless Steel									
LS-4.6-200B	7.9	201.0	0.18	4.6	2	51	100	45.3	100
LS-4.6-360B	14.2	360.0	0.18	4.6	4	102	100	45.3	100
LS-4.6-520B	20.5	520.0	0.18	4.6	6	152	100	45.3	100
LS-4.6-680B	26.7	679.0	0.18	4.6	8	203	100	45.3	100
LS-4.6-840B	33.0	838.0	0.18	4.6	10	254	100	45.3	100
LS-7.9-200B	7.9	201.0	0.31	7.9	3	51	250	113.3	50
LS-7.9-360B	14.2	360.0	0.31	7.9	4	102	250	113.3	50
LS-7.9-520B	20.5	520.0	0.31	7.9	6	152	250	113.3	50
LS-7.9-680B	26.7	679.0	0.31	7.9	8	203	250	113.3	50
LS-7.9-840B	33.0	838.0	0.31	7.9	10	254	250	113.3	50
LS-7.9-1010B	41.3	1050.0	0.31	7.9	12.5	318	250	113.3	50