


Catamount®



T&B Catalog Number: TT-11-50-9-C
UPC Number: 72849414304
Description: 11IN 50 LB TWIST TAIL NAT.CABLE TIE

Status: H

Features

Designed for quick, easy, tool-less installation. After installing, remove excess tail with a simple "bend, bend again and twist" motion.

General

Material Nylon 6.6
Color White

Dimension Information

Length (inches) 11.7
Width (inches) 0.187
Max. Wire Bundle Diameter (inches) 1 3/4

Specifications

Tensile Strength (lbs.) 50
Temperature Rating -40°F to 185°F
Flammability Rating UL 94 V-2

Packaging

T&B Order Multiple 100
T&B Inner Pack 100
Package in Units 5000
Package Type Standard
T&B Sold in UOM Each
T&B Weight Per UOM 5.23 lbs. per 1000

Application Support

Overview Available on Website

Certifications

RoHS Compliance Yes

Catamount® Cable Ties



Releasable Ties



CAT. NO.	LENGTH (IN.)	MAX. BUNDLE DIA.	COLOR	STD. QTY.
L-5-50R-9-C	5.9	1/4	Natural	100
L-5-50R-0-C	5.9	1/4	Black	100
L-8-50R-9-C	7.8	2	Natural	100
L-8-50R-0-C	7.8	2	Black	100
L-10-50R-9-C	11.265	3	Natural	100
L-10-50R-0-C	11.265	3	Black	100

Bulk packages available. Contact Customer Service. Push button release.



Mounting Head Ties

CAT. NO.	LENGTH (IN.)	MAX. BUNDLE DIA.	WIDTH (IN.)	MIN. LOOP TENSILE	MOUNTING HEAD SCREW SIZE	COLOR	STD. QTY.
L-5-30MH-9-C	5.85	1/4	.140	30	No. 8	Natural	100
L-5-30MH-0-C	5.85	1/4	.140	30	No. 8	Black	100
L-7-50MH-9-C	7.5	1/4	.185	30	No. 10	Natural	100
L-7-50MH-0-C	7.5	1/4	.185	30	No. 10	Black	100
L-11-50MH-9-C	11.1	3	.187	50	No. 10	Natural	100
L-11-50MH-0-C	11.1	3	.187	50	No. 10	Black	100
L-14-50MH-9-C	14.5	4	.187	50	No. 10	Natural	100
L-14-50MH-0-C	14.5	4	.187	50	No. 10	Black	100
L-14-120MH-9-C	14.85	4	.300	120	1/4"	Natural	100
L-14-120MH-0-C	14.85	4	.300	120	1/4"	Black	100

Bulk packages available. Contact Customer Service. Use GC-100, L-200, L-400-C, EPO-120 or EPO-50 Installation Tool



Push Mount Cable Ties



CAT. NO.	LENGTH (IN.)	MOUNTING HOLE	MAX. PANEL THICKNESS	MAX. BUNDLE DIA.	COLOR	STD. QTY.
L-5-50PM-9-C	5.8	.250	.105	1	Natural	100
L-5-50PM-0-C	5.8	.250	.105	1	Black	100
L-7-50PM-9-C	8.2	.250	.105	1/4	Natural	100
L-7-50PM-0-C	8.2	.250	.105	1/4	Black	100

Bulk packages available. Contact Customer Service.

Use GC-100, L-200, L-400-C Installation Tool

Black shown

Releasable Push Mount Cable Ties



CAT. NO.	LENGTH (IN.)	MOUNTING HOLE	MAX. PANEL THICKNESS	MAX. BUNDLE DIA.	COLOR	STD. QTY.
L-5-50PMR-9-C	5.8	.250	.105	1	Natural	100
L-5-50PMR-0-C	5.8	.250	.105	1	Black	100
L-7-50PMR-9-C	8.2	.250	.105	1/4	Natural	100
L-7-50PMR-0-C	8.2	.250	.105	1/4	Black	100

Bulk packages available. Contact Customer Service.

Use GC-100, L-200, L-400-C Installation Tool

Tail twists right off — no tools needed!

TwistTail™



- Unique, patent-pending design for quick, easy, tool-less installation
- After installing, remove excess tail with a simple "bend, bend again and twist" motion
- Tail breaks off neat and clean — no sharp edges to damage hands or cables
- Ideal for limited-space installations where you can't fit a cut-off tool
- Suitable for any general-purpose cable tie application
- Available in white or UV resistant black 6.6 nylon



CAT. NO.	LENGTH (IN.)	MIN. TENSILE STRENGTH (LBS.)	COLOR	STD. QTY.
TT-7-50-9-C	7	50	White	100
TT-7-50-0-C	7	50	Black	100
TT-11-50-9-C	11	50	White	100
TT-11-50-0-C	11	50	Black	100
TT-14-50-9-C	14	50	White	100
TT-14-50-0-C	14	50	Black	100