

CATALOG

➔ **Cross Reference**

- [Competitive Products](#)
- [Military Spec P/Ns](#)
- [Tyco Brand P/Ns](#)

- ➔ [Part Number Search](#)
- ➔ [Document Search](#)
- ➔ [Product Type Search](#)
- ➔ [Product Family Search](#)
- ➔ [Alphabetical Search](#)
- ➔ [RoHS/ELV Compliance & Alternates](#)
- ➔ [CAD Model Search](#)
- ➔ [Brand Search](#)
- ➔ [Tool Search](#)
- ➔ [Multiple Part Comparison](#)
- ➔ [Lead Free Solutions](#)
- ➔ [Help/Glossary](#)

[Home](#)

e-bulletin newsletter
SUBSCRIBE NOW!
 click here

Terminals and Splices

➔ **Ring and Spade Tongue Terminals**



35108

✔ [Active](#)

Directive 2002/95/EC Compliant

[RoHS Compliant](#)

(Corporate P/N: 35108)

[Search for Parts](#)

Document links for this part cannot be displayed. Your browser does not support inline frames or is currently configured not to display inline frames. Inline frames are supported in both Internet Explorer 5 and Netscape 6, as well as all later versions of these browsers.

Related Part Information		
General Information	eCommerce	Related Part Information
<ul style="list-style-type: none"> ➤ General Info ➤ Sales Info ➤ Assembly Subcontractors 	<ul style="list-style-type: none"> ➤ Pricing & Availability 	<ul style="list-style-type: none"> ➤ Tooling

Photos & Line Drawings - The photographs and/or line drawings are representative images of a product for viewing purposes only.

[Product Photo](#)

Searchable Features:	
Brand:	AMP
Government/Industry Qualification:	Yes
Government/Industry Part Number:	MS25036-156, AS25036-156
RoHS/ELV Compliance:	RoHS compliant, ELV compliant
Lead Free Solder Processes:	Not relevant for lead free process
Terminal Shape:	Ring Tongue
Receptacle Style:	Straight
Body Style:	PIDG
Barrel Type:	Closed Barrel
Wire/Cable Type:	Regular Wire

Other Properties:	
Class:	1 & 2
Voltage (VAC):	300
Tongue Material Thickness (mm [in]):	1.02 [0.040]
Color:	Yellow
Insulation Material:	Nylon
Packaging Quantity:	500
Temperature Range (°C):	105
Comment:	Available On-Tape for Automatic Termination.

<u>Wire Range (mm [AWG]):</u>	2.62-6.64 ² [12-10]
Wire Range (CMA):	5,180 – 13,100
<u>Insulation:</u>	Yes
<u>Insulation Support:</u>	Insulation Support
<u>Insulation Diameter (mm [in]):</u>	3.81-6.35 [.150-.250]
Stud Size:	8 [M4]
<u>Stud Diameter (mm [in]):</u>	4.34 [0.171]
<u>Shape:</u>	RING-041
<u>Heavy Duty:</u>	No
<u>Packaging Method:</u>	Loose Piece
<u>Material:</u>	Copper
<u>Finish:</u>	Tin

[Copyright](#) and [Privacy Statement](#)
Visit [Tyco International Ltd.](#)

[[Products](#) | [Catalog](#) | [Brands](#) | [Industries](#) | [Commerce](#) | [Supplier](#) | [Contact Us](#) | [About](#) | [Home](#)]