





T&B Catalog Number: UPC Number: **Description:**

TY28MX 78621082484 Cable Tie 50lb 14" Ultraviolet Resistant Black Nylon with Stainless Steel Locking Device Bulk Pack

Status:

General	
Material	Nylon 6.6 Weather Resistant
Color	Black
Dimension Information	
Length (inches)	14.2
Width (inches)	.187
Max. Wire Bundle Diameter (inches)	4
Specifications	
Military Standard Part No.	MS3367-2
Tensile Strength (lbs.)	50
Temperature Rating	-40°F to 185°F
Flamability Rating	UL 94 V-2
Tooling	
Application Tools	ERG50, WT1-TB
Packaging	
T&B Order Multiple	1000
T&B Inner Pack	1000
Package in Units	5000
Package Type	Bulk
T&B Sold in UOM	Each
T&B Weight Per UOM	0.56 lbs. per 100
Application Support	
Overview	Available on Website
Material Selection Guide	Available on Website
Available Colors	Available on Website
Certifications	
RoHS Compliance	Yes

Active

Ty-Rap[•] Cable Fastening Systems

Cable Ties

Cable ties at your fingertips!

Ty-Rap Tote[®] 4", 8" and 11"–14" Combination Length Cable Tie Dispensers

- Durable, lightweight polyester exterior and tough vinyl interior construction
- Rugged diamond-shaped cutout for easy access to cable ties (up to 8", 11"-14" lengths) and rectangular-shaped (for 4" length)
- · Handy belt clip and chrome steel loop for easy attachment
- · Resealable hook-and-loop flap for easy refill
- · Includes 100 genuine Ty-Rap" cable ties



STD PKG. CAL NO.	DESCRIPTION	STD. PKG. QTY.
TY-TOTE-25	Ty-Rap Tote [®] 8" Cable Tie Dispenser (Includes 1 pkg. TY525M)	1
TY-TOTE-23	Ty-Rap Tote" 4" Cable Tie Dispenser (includes 1 pkg. TY523M)	1
TY-TOTE-28	Ty-Rap Tote" 11"-14" Cable Tie Dispenser (Includes 1 pkg. TY528M)	1

Order only genuine Ty-Rap* Cable Ties to refit your dispensent

Ty-Rap® Nylon 6.6 Cable Ties — Weather Resistant



TENGIE E

BUILTINGS



TY5272MX — Tie body width .270"

STD. PKG. Cat. No.	BULK PKG. Cat. No.	WIDTH N./MM.	LENGTH INJ/MML	BUNDLE DIA.	STANDARD PART NO.	STRENGTH LBS./N.	STD. PKG. QTY.	BULK PKG. QTY.
TY523MX	TY23MX	.09/2.29	3.62/91.95	.63/16.00	MS3367-4	18/90.07	100	1,000
TY52315MX	TYB2315MX	.09/2.29	7.00/177.80	1.50/38.10	_	18/80.07	100	1,000
TY5232MX	TY232MX	.09/2.29	8.00/203.20	2.00/50.80	—	18/80.07	100	1,000
TY5234MX	TY234MX	.09/2.29	14.00/355.60	4.00/101.60	_	18/80.07	100	1,000
TY524MX	TY24MX	.14/3.56	5.50/139.70	1.13/28.70	MS3367-5	40/177.90	100	1,000
TY5242MX	TY242MX	.14/3.56	8.19/208.03	2.00/50.80	_	40/177.90	100	1,000
TY526MX	TY26MX	.14/3.56	11.10/281.94	3.00/76.20	-	30/133.40	100	1,000
TY5244MX	TY244MX	.14/3.56	14.50/368.30	4.00/101.60	_	30/133.40	100	1,000
TY525MX	TY25MX	.19/4.83	7.31/185.67	1.75/44.45	MS3367-1	50/222.40	100	1,000
TY5253MX	TY253MX	.19/4.83	11.60/294.64	3.00/76.20	MS3367-7	50/222.40	100	1,000
TY528MX	TY28MX	.19/4.83	14.20/360.68	4.00/101.60	MS3367-2	50/222.40	100	1,000
TY5272MX*	TY272MX*	.27/6.86	8.75/222.250	2.00/50.80	_	120/533.80	50	500
TY527MX	TY27M0	.27/6.86	13.40/340.36	3.50/88.90	MS3367-3	120/533.80	50	500
TY5275MX	TY275MX	.27/6.86	18.00/457.20	5.00/127.00	_	120/533.80	50	500
TY5277MX	TY277MX	.27/6.86	24.30/617.22	7.00/177.80	—	120/533.80	50	500
TY529MX	TY29MX	.27/6.86	30.00/762.00	9.00/228.60	MS3367-6	120/533.80	50	500
TY53510MX	-	.32/8.13	35.00/889.00	10.00/254.00	—	175/778.40	50	-
TY54513MX*	-	.32/8.13	45.00/1143.00	13.00/330.20	_	175/778.40	50	_

MAX MODE

For use in temperatures ranging from -40° F to 185° F (-40° C to 85° C).

* For military compliance of weather-maistant black 120-lb. des, replace auffir X with O (i.e., 1927M-Q.

- † Not [®] Listed or Recognized Models.
- Black color