

You Searched for product number CME2425-1 .
The Triad Magnetics product is highlighted below.



Triad Transformer Catalog

SWITCHMODE/HIGH FREQUENCY - COMMON MODE INDUCTORS

Description:

Highly dependable TRIAD common mode EMI suppression inductors manufactured by Triad Magnetics are used in various types of power supplies to eliminate noise common to all lines. These units also provide effective differential mode filtering. Meeting VDE, IEC, UL, and CSA requirements, they minimize AC line transmitted interference often created by high frequency switching power supplies. Normally placed close to the input power source, these compact inductors are constructed with UL rated 130°C materials.




Figure A




Figure B




Figure C




Figure D

- [PRODUCTS]
- [SALES CHANNELS]
- [COMPANY]
- [CONTACT]
- [HOME]

PRINT PAGE

CLOSE PAGE

E-CORE INDUCTORS

Type No.	Figure	Inductance mH min.	Amps R.M.S.	Max. DC Resistance	Min. Leakage	Dimensions							Wt. Lbs.
						H	W	L	A	B	C	D	
CME375-1	A	4.40	5.500	.049 Ohms	45.0 µH	1.18	1.26	1.50	.150	.600	.200	.036 Sq.	.054
CME375-2	A	6.90	4.400	.077 Ohms	70.0 µH	1.18	1.26	1.50	.150	.600	.200	.036 Sq.	.054
CME375-3	A	10.9	3.500	.122 Ohms	125.0 µH	1.18	1.26	1.50	.150	.600	.200	.036 Sq.	.054
CME375-4	A	17.8	2.700	.196 Ohms	180.0 µH	1.18	1.26	1.50	.150	.600	.200	.036 Sq.	.054
CME375-5	A	28.6	2.200	.316 Ohms	300.0 µH	1.18	1.26	1.50	.150	.600	.200	.036 Sq.	.054
CME375-6	A	43.6	1.750	.489 Ohms	440.0 µH	1.18	1.26	1.50	.150	.600	.200	.036 Sq.	.054
CME375-7	A	70.3	1.380	.785 Ohms	720.0 µH	1.18	1.26	1.50	.150	.600	.200	.036 Sq.	.054
CME375-8	A	111.6	1.100	1.240 Ohms	1.1 mH	1.18	1.26	1.50	.150	.600	.200	.036 Sq.	.054
CME375-9	A	176.1	.087	1.980 Ohms	1.8 mH	1.18	1.26	1.50	.150	.600	.200	.036 Sq.	.054
CME2425-1	B	1.05	2.50	.050 Ohms	9.0 µH	1.075	1.050	1.050	.125	.800	.610	.029 Sq.	.154
CME2425-2	B	2.37	2.00	.080 Ohms	14.0 µH	1.075	1.050	1.050	.125	.800	.610	.029 Sq.	.154
CME2425-3	B	3.8	1.60	.127 Ohms	25.0 µH	1.075	1.050	1.050	.125	.800	.610	.029 Sq.	.154
CME2425-4	B	6.0	1.28	.202 Ohms	36.0 µH	1.075	1.050	1.050	.125	.800	.610	.029 Sq.	.154
CME2425-5	B	9.8	1.00	.319 Ohms	60.0 µH	1.075	1.050	1.050	.125	.800	.610	.029 Sq.	.154
CME2425-6	B	16.0	0.80	.500 Ohms	90.0 µH	1.075	1.050	1.050	.125	.800	.610	.029 Sq.	.154
CME2425-7	B	27.7	0.63	.820 Ohms	144.0 µH	1.075	1.050	1.050	.125	.800	.610	.029 Sq.	.154
CME2425-8	B	40.5	0.50	1.260 Ohms	240.0 µH	1.075	1.050	1.050	.125	.800	.610	.029 Sq.	.154
CME2425-9	B	67.5	0.40	2.020 Ohms	360.0 µH	1.075	1.050	1.050	.125	.800	.610	.029 Sq.	.154

ENCAPSULATED TOROIDAL INDUCTORS

Type No.	Figure	Min. Inductance	Amps R.M.S.	Max. DC Resistance	Min. Leakage	Dimensions					Wt. Lbs.
						H	W	L	A	B	
CMT908-V1	C	2.00 mH	7.50	.020 Ohms	25.0 μ H	1.50	.800	1.45	.9	.6	.08
CMT908-V2	C	4.00 Mh	5.20	.040 Ohms	45.0 μ H	1.50	.800	1.45	.9	.6	.08
CMT908-V3	C	8.00 mH	3.20	.120 Ohms	90.0 μ H	1.50	.800	1.45	.9	.6	.08
CMT908-V4	C	16.00 mH	2.60	.160 Ohms	180.0 μ H	1.50	.800	1.45	.9	.6	.08
CMT908-H1	D	2.00 mH	7.50	.020 Ohms	25.0 μ H	.80	1.5	1.5	1.08	1.28	.120
CMT908-H2	D	4.00 Mh	5.20	.040 Ohms	45.0 μ H	.80	1.5	1.5	1.08	1.28	.120
CMT908-H3	D	8.00 mH	3.20	.120 Ohms	90.0 μ H	.80	1.5	1.5	1.08	1.28	.120
CMT908-H4	D	16.00 mH	2.60	.160 Ohms	180.0 μ H	.80	1.5	1.5	1.08	1.28	.120

Technical Notes:

1. Hi-pot tested at 2,500 VRMS.
2. DC resistance at 20°C +/- 10%.
3. Inductances are minimum measured at 10 Gauss.
4. Current ratings for approximately 40°C temperature rise.




Figure A




Figure B




Figure C




Figure D