



## Model #: INTERNET350U

**Internet Office UPS System - Affordable full system protection for PCs and workstations**



### Highlights

- 350VA ultra-compact UPS
- Maintains 120V nominal output during blackouts
- Workstation optimized features include HID-compliant USB port, single line TEL / DSL line surge suppression and three surge-only outlets
- Space saving right-angle input plug
- Input: NEMA 5-15P (120V 15A) / Output: 6 NEMA 5-15R (120V)
- 2 year product warranty

### Description

Tripp Lite's INTERNET350U standby UPS system offers complete protection from blackouts, brownouts and transient surges on both AC and dialup modem lines. Provides seamless battery support during brownouts and power failures with enough runtime to save and shutdown connected equipment without data loss. Offers complete power protection in an ultra-compact, flat-pack housing with an appearance closer to a power strip than other bulky UPS designs. Includes 3 battery supported outlets for computer, monitor and one vital system peripheral, plus 3 additional surge suppression-only outlets for printers and other system accessories not requiring battery support. USB port enables optional unattended system shutdown without data loss in the case of extended power failure.

includes bundled USB cable. Built-in single line RJ11 phone suppression jacks with line splitter protects up to two directly connected modems, fax machines, cordless phones or other peripherals with a standard dialup phone connection. Built-in audible alarm and front panel LEDs offer continuous status information regarding line and battery power operation. 350VA/180 watt power handling ability supports entry-level PC systems for up to 15 minutes during power fail conditions. 2 year warranty.

### Applications

Basic desktop PCs for home/home-office use, network terminals, audio/video and home entertainment systems and other sensitive electronic devices.

### Package Includes

- INTERNET350U UPS System
- USB communications cable
- Instruction manual with warranty information

### Features

- INTERNET350U standby UPS offers complete protection from blackouts, brownouts and surges on both AC and TEL/DSL line connections
- 6 widely spaced outlets accommodate large transformer plugs without blocking outlets
- 3 battery supported outlets protect computer, monitor and vital system peripherals, plus 3 additional surge suppression-only outlets for printers and other system accessories not requiring battery support
- Provides battery derived AC output during blackouts and brownouts
- 350VA/180 watt power handling ability supports a variety of PCs, workstations and other sensitive electronics
- Supports entry-level PC systems up to 12 minutes during blackout conditions

Built-in single line TEL/DSL line surge suppression protects modems, fax machines or cordless phones on a single phone line connection  
 USB port, free PowerAlert software (available via web download) and cabling offer safe unattended shutdown without data loss during extended outages

HID-compliant USB interface enables integration with built-in power management and auto-shutdown features of Windows and Mac OS X.

Supports Tripp Lite's Watchdog system service to restore operation to locked equipment through soft reboot of application/OS or hard power off/on reboot of connected equipment - ideal for unattended kiosk applications

Space saving, ultra-compact housing fits almost anywhere

## Specifications

<b>SYSTEM OVERVIEW</b>	
<b>Voltage compatibility</b>	120VAC
<b>Frequency compatibility</b>	60Hz
<b>OUTPUT</b>	
<b>Output VA</b>	350
<b>Output watts</b>	180
<b>Output nominal voltage</b>	120VAC
<b>Output voltage regulation</b>	BATTERY MODE: PWM sine wave output 115V +/-5%
<b>Output frequency regulation</b>	LINE MODE: Passes line frequency of 60Hz +/-10% BATTERY MODE: Inverter output regulated to 60Hz +/-0.5Hz
<b>Outlet quantity / type</b>	6 NEMA 5-15R
<b>INPUT</b>	
<b>Maximum input amps</b>	10A / 1200 watts
<b>Input connection type</b>	NEMA 5-15P
<b>Input cord length</b>	6 ft., 18 gauge
<b>Recommended Electrical Service</b>	15A 120V
<b>BATTERY</b>	
<b>Full load runtime</b>	3 minutes (350VA)
<b>Half load runtime</b>	11 minutes (175VA)
<b>DC system voltage</b>	12 VDC
<b>Typical battery lifespan</b>	3-6 years, depending on usage
<b>Battery recharge rate</b>	2-4 hours to 90%
<b>LEDS ALARMS &amp; SWITCHES</b>	
<b>Front panel LEDs</b>	2 LEDs indicate line power, battery power status
<b>Alarms</b>	Audible alarm beeps at regular intervals to indicate battery backup operation. Alarm also sounds during self-test operation.
<b>Switches</b>	Combination power off / on / self-test push button switch
<b>SURGE / NOISE SUPPRESSION</b>	
<b>AC surge suppression</b>	380 joules
<b>AC suppression response time</b>	Instantaneous
<b>Dataline suppression</b>	TEL/DSL
<b>EMI / RFI AC noise suppression</b>	Yes, >40dB @ 1 MHz
<b>PHYSICAL</b>	

Shipping weight (lbs)	5.8
Shipping weight (kg)	2.6
Shipping Dimensions (HWD/in)	4.1 x 11.3 x 7.7
Shipping Dimensions (HWD/cm)	10.4 x 28.7 x 19.6
Unit weight (lbs)	5
Unit weight (kg)	2.3
Unit Dimensions (HWD/in)	3 x 8 x 4.6
Unit Dimensions (HWD/cm)	7.6 x 20.3 x 11.7
Material of construction	ABS
Form factors supported	Ultra-compact
Integrated keyhole mounting tabs	Yes, keyhole slots allow for secure wall-mounting installation
<b>ENVIRONMENTAL</b>	
Operating Temperature	+32 to +104 degrees Fahrenheit / 0 to +40 degrees Celsius
Storage Temperature	+5 to +122 degrees Fahrenheit / -15 to +50 degrees Celsius
Relative Humidity	0 to 95%, non-condensing
Line mode BTU/hr. (Max.)	46.27
<b>COMMUNICATIONS</b>	
Network monitoring port	USB (HID-compliant)
Software and cabling included	Includes USB interface cable, PowerAlert software available via free download
WatchDog compatibility	Yes, compatible with Tripp Lite's Watchdog system service to restore operation to locked equipment through soft reboot of application / OS or hard power off/on reboot of connected equipment - ideal for unattended kiosk applications
<b>LINE / BATTERY TRANSFER</b>	
Transfer time from line power to battery mode	2-4 milliseconds
Low voltage transfer to battery power	Switches to battery power as line voltage decreases to 98 volts or less. Resets back to line power mode as line voltage increases to 103V or higher.
High voltage transfer to battery power	Switches to battery power as line voltage increases to 139V or higher. Resets back to line power mode when line voltage decreases to 135V or lower.
<b>SPECIAL FEATURES</b>	
Cold Start	Yes, inverter can be "cold started" to enable temporary AC output during a power failure
Appearance	Attractive black ultra-compact housing
<b>CERTIFICATIONS</b>	
Certifications	Tested to UL1778 (USA), Tested to CSA (Canada), Class B (Emissions), NOM (Mexico), FCC Part 68 / Industry Canada (telecommunications)
<b>WARRANTY</b>	
Product warranty	2 years

**Optional coverage**

Optional 3 and 5 year on site or factory warranties available for select opportunities, contact Tripp Lite for more information

**Related Items****Audio Cables**

CT120	Instant-Read- AC Outlet Circuit Tester	Qty: [optional]
-------	--	-----------------

**Extended Warranties**

WEXT3-INTERNET	3-Year Extended Warranty - For Internet Office Models	Qty: [optional]
----------------	---	-----------------

WEXT5-INTERNET	5-Year Extended Warranty - For Internet Office Models	Qty: [optional]
----------------	---	-----------------

**Software**

WATCHDOGSW	WatchDog Service Monitoring / Reboot Software	Qty: [optional]
------------	---	-----------------

**Surge Protectors**

DTEL2	Network Surge Suppressor - Essential protection for data and communication lines	Qty: [optional]
-------	--	-----------------

DNET1	Network Surge Suppressor - Essential protection for data and communication lines	Qty: [optional]
-------	--	-----------------

DCATV	Network Surge Suppressor - Essential protection for TV/VCR coaxial lines	Qty: [optional]
-------	--	-----------------

**USB Cables & Adapters**

U005-10I	USB Gold Extension cable - USB "A" Right Angle Male to USB "A" Female - 10"	Qty: [optional]
----------	---	-----------------

**USB Hubs/Accessories**

U222-004-R	USB Hubs - 4-Port USB 2.0 Certified Ultra-Mini Hub	Qty: [optional]
------------	--	-----------------