



Model #: PDU1415

Basic PDU / Power Distribution Unit - Safe, reliable power distribution for critical networking equipment

Highlights

- 24 inch PDU supports vertical, horizontal or wallmount installation
- 14 NEMA 5-15R outlets
- 15 foot AC input cord with NEMA 5-15P plug
- 15A circuit breaker
- Switchless design



Description

Tripp Lite's
are configurable f
area of most ra
UPS or g
breaker, grounding lug and rugged all-metal case design.

PLUG/OUTLETS - Input: NEMA 5-15P/Output: 14 NEMA5-15R

ELECTRICAL - 120V AC, 50/60Hz, 15A (Requires NEMA 5-15R wall receptacle)

FORMAT - 24 inch mountable strip format

Applications

- Multi-
- internetworkin
- or commercially derived AC power to protected equipment.

Package Includes

- PDU1415 power strip
- Instruction manual with warranty information

Features

- Corded AC power distribution unit with 15 amp capacity and 14 AC receptacles
- Versatile
- closets and wallmount applications
- U
- 14 NEMA5-15R output receptacles accept common NEMA5-15 equipment plugs
- 15 foot AC cord NEMA5-15P plug connection
- Switch-free design prevents the potential for accidental shutoff of connected loads
- 15 amp electrical capacity with circuit breaker

120V AC, 50/60Hz electrical compatibility

Specifications

| SYSTEM OVERVIEW | |
|-----------------------------------|---|
| Voltage compatibility | 120V |
| Frequency compatibility | 50 / 60Hz |
| OUTPUT | |
| Output watts | 1800 |
| Output nominal voltage | 120V |
| Outlet quantity / type | 14 NEMA 5-15R |
| Overload protection | 15A |
| INPUT | |
| Maximum input amps | 15A |
| Input connection type | NEMA 5-15P |
| Input cord length | 15 ft. |
| Recommended Electrical Service | 120V |
| LEDS ALARMS & SWITCHES | |
| Switches | No switch |
| PHYSICAL | |
| Shipping weight (lbs) | 5.2 |
| Shipping weight (kg) | 2.4 |
| Shipping Dimensions (HWD/in) | 2.75 x 27.25 x 8.25 |
| Shipping Dimensions (HWD/cm) | 7 x 69.2 x 21 |
| Unit weight (lbs) | 4.6 |
| Unit weight (kg) | 2.1 |
| Unit Dimensions (HWD/in) | 1.75 x 25.75 x 2.25 |
| Unit Dimensions (HWD/cm) | 4.45 x 65.4 x 5.7 |
| Material of construction | Steel |
| Form factors supported | Vertical or horizontal mounting supported in wallmount applications, racks and a variety of other surface types |
| Style | Rackmount, Vertical Rackmount, Wallmount/Under-Counter |
| CERTIFICATIONS | |
| Certifications | Tested to UL60950-1 (USA) and CAN/CSA C22.2 No. 60950-1-03 (Canada) |
| WARRANTY | |
| Product warranty | Lifetime |