



Model #: PDUMV20

Metered PDU / Power Distribution Unit - Safe, reliable power distribution with digital current meter



Highlights

- Digital current meter display
- 20 outlets
- Convenient and safe covered, on/off switch
- 20-amp circuit breaker
- 15-ft. AC power cord
- 60 inch length
- Toolless button mount installation

Description

Tripp Lite's PDUMV20 metered power distribution unit offers 20 amp, 120V multi-outlet AC power distribution in a convenient 60 inch mountable housing. Digital current meter displays the power consumption of connected equipment. Offers vertical power distribution in rackmount, raceway, and workbench applications. Toolless installation supports fast installation in button-mount compatible equipment racks. Sturdy all-metal extruded aluminum housing stands up to demanding network, laboratory, or factory environments. Unfiltered electrical pass-through makes the PDUMV20 ideal for distributing alternate waveform UPS or generator power in rack enclosures, network closets and more. Includes 20 NEMA 5-15/20R output receptacles, 15 ft. AC line cord, lighted power switch with locking transparent cover to prevent accidental shutoff, and 20 amp circuit breaker in rugged metal case design.

PLUG/OUTLETS-Input: NEMA L5-20P/Output: 20 NEMA 5-15/20R

ELECTRICAL- 120V AC, 50/60Hz, 20A [Requires NEMA L5-20R or 5-20R(using included adapter) wall receptacle]

FORMAT- 60 inch mountable strip format

Applications

- Offers vertical or horizontal multi-outlet power distribution in rack enclosures, raceways, desktops and more. Ideal for distribution of alternate, sinewave UPS and generator power, or commercially derived AC power to connected equipment.

Package Includes

- PDUMV20 Metered Vertical PDU
- (1) L5-20P to 5-20P plug adapter
- Mounting hardware
- Six protective outlet covers
- Instruction manual with warranty information

Features

- Corded AC power distribution unit with 20 amp capacity and 20 AC receptacles
- Digital current meter display
- Sturdy 60 inch aluminum housing

- Toolless installation supports fast installation in button-mount compatible equipment racks
- Included hardware allows for Zero-U configurations in rack enclosures
- Ideal for horizontal or vertical raceway style power distribution in office, workbench, industrial, network, and telecom applications
- Lighted power switch with locking transparent safety cover prevents accidental shutoff
- 20 amp electrical capacity
- 120V AC, 50/60Hz electrical compatibility
- 15 ft. power cord
- Lifetime warranty

Specifications

OVERVIEW	
Model Type	Metered
SYSTEM OVERVIEW	
Voltage compatibility	120V
OUTPUT	
Frequency compatibility	50 / 60 Hz
Output VA	20A
Output watts	2400 watts
Output nominal voltage	120V
Overload protection	20A
Outlet quantity / type	20 NEMA 5-15/20R
INPUT	
Recommended Electrical Service	120V
Maximum input amps	20A
Input connection type	NEMA L5-20P with NEMA 5-20P plug adapter
Input cord length (ft.)	15 ft.
LEDS ALARMS & SWITCHES	
Switches	Lighted on/off switch with integrated transparent safety cover
Front panel LEDs	Digital ammeter display
PHYSICAL	
Shipping weight (lbs)	5.9
Unit Dimensions (HWD/in)	1.75 x 60 x 1.25
Shipping Dimensions (HWD/in)	3 x 63.25 x 2.75
Unit weight (lbs)	5.2
Material of construction	Aluminum
Style	Vertical Rackmount
Form factors supported	Vertical
SPECIAL FEATURES	
Appearance	Black housing with digital current meter display

CERTIFICATIONS**Certifications**

Tested to UL60950-1 (USA) and CAN/CSA C22.2 No. 60950-1-03 (Canada), RoHS Compliant

WARRANTY**Product Warranty Period
(U.S., Canada & Puerto Rico)**