

# Model #: PS-415-HGULTRA

## Power Strip - Agency-Approved Medical-Grade Outlet Strip



## **Highlights**

Fully tested, certified and compliant with UL 60601-1 and UL 60950-1 Internal site-wiring fault protection

4 hospital-grade outlets with safety covers Switchless design prevents accidental shutoff

15-ft. cord with hospital-grade plug

Rugged all-metal case

#### **Description**

Offering 15A A

a variety o□

7,375,939) internal

prevent acc□

circuit breaker, and optional-use keyhole mounting slots and flanges.

#### Applications

AC power distribut□

areas where NEC requires hospital-grade receptacles

#### Package Includes

PS-415-HGULTRA Medical-Grade Power Strip

Owner's manual with warranty information

#### **Features**

Unique internal site-wiring fault protection

Rugged all-metal housing stands up to the most demanding environments

4 x NEMA 5-15R-HG outlets with safety covers

15-ft. cord with NEMA 5-15P-HG plug

Switchless design prevents accidental shutoff

15A circuit breaker

Multiple installation options with intergral mounting flanges and slots

UL60601-1 and UL 60950-1 compliant

U.S. Patent No. 7,375,939

### **Specifications**

SYSTEM OVERVIEW	
Voltage compatibility	120VAC

Frequency compatibility	50/60 Hz	
OUTPUT		
Output volt amp capacity (amps)	15A	
Outlet quantity / type	4 x NEMA 5-15R-HG Hospital-Grade	
Outlet orientation	Single row of 4	
Overload protection	15A resettable circuit breaker	
Outlet safety covers	Yes	
INPUT		
Input connection type	NEMA 5-15P-HG Hospital-Grade	
Input cord length (ft.)	15	
Input cord length (m)	4.572	
Recommended Electrical Service	15A 120V	
LEDS ALARMS & SWITCHES		
Switches	No power switch	
PHYSICAL		
Unit weight (lbs)	3.2	
Unit weight (kg)	1.5	
Unit Dimensions (HWD/in)	1.5 x 13.75 x 2.5	
Unit Dimensions (HWD/cm)	3.8 x 34.9 x 6.4	
Material of construction	Metal	
Integrated keyhole mounting tabs	Yes	
Receptacle Color	White	
AC line cord color	White	
SPECIAL FEATURES		
Appearance	Attractive all-white color scheme	
CERTIFICATIONS		
Approvals	TUV tested to UL 60601-1 and UL 60950-1 (USA); TUV tested to CAN/CSA-C22.2 No. 601.1-M90 and 60950-1-03 (Canada)	
WARRANTY		
Product warranty	Lifetime	