



## Model #: PS-606-HG

### Power Strip - With Hospital-Grade Plug & Receptacles



#### Highlights

- Versatile power distribution strip
- 6 hospital-grade outlets and hospital-grade plug
- 6-ft. cord
- 15A resettable circuit breaker
- UL, cUL approved

#### Description

Tripp Lite's PS-606 hospital-grade receptacle keyhole mounting tabs and flanges.

PLUG/OUTLETS: NEMA 5-15P-HG hospital-grade plug and 6 NEMA 5-15R-HG hospital-grade receptacles

ELECTRICAL: 120V AC, 50/60 Hz, 15A

FORMAT: all-metal corded multi outlet strip

#### Applications

- AC power distribution hospital-grade receptacles.

#### Package Includes

- PS-606-HG Power Strip
- User manual with warranty information

#### Features

- Rugged all-metal housing withstands years of use without breakage
- 6 x NEMA 5-15R-HG hospital-grade receptacles
- 6-ft. AC cord with integrated, molded NEMA 5-15P-HG hospital-grade plug
- Optional-use keyhole mounting tabs and flanges
- Switchless design prevents accidental shutoff
- 15A electrical capacity with built-in resettable circuit breaker
- 120V, 50/60 Hz electrical compatibility
- Certified by UL (USA) and cUL (Canada)

#### Specifications

##### SYSTEM OVERVIEW

|                                   |  |
|-----------------------------------|--|
| Voltage compatibility             | 120V AC  |
| Frequency compatibility           | 50/60 Hz   |
| <b>OUTPUT</b>                     |  |
| Output volt amp capacity (amps)   | 15A  |
| Outlet quantity / type            | 6 x NEMA 5-15R-HG Hospital Grade   |
| Outlet orientation                | Single row of 6  |
| Overload protection               | 15A circuit breaker  |
| <b>INPUT</b>                      |  |
| Input connection type             | NEMA 5-15P-HG Hospital Grade   |
| Input cord length (ft.)           | 6  |
| Input cord length (m)             | 1.83   |
| Recommended Electrical Service    | 15A, 120V  |
| <b>LEDS ALARMS &amp; SWITCHES</b> |  |
| Switches                          | No power switch  |
| <b>PHYSICAL</b>                   |  |
| Shipping weight (lbs)             | 3.5  |
| Shipping weight (kg)              | 1.6  |
| Unit weight (lbs)                 | 2.4  |
| Unit weight (kg)                  | 1.1  |
| Unit Dimensions (HWD/in)          | 1.5 x 13.75 x 2.5  |
| Unit Dimensions (HWD/cm)          | 3.8 x 34.9 x 6.4   |
| Material of construction          | Metal  |
| Integrated keyhole mounting tabs  | Keyhole mounting tabs and flanges enable mounting to a variety of surfaces |
| Receptacle Color                  | White  |
| AC line cord color                | White  |
| <b>CERTIFICATIONS</b>             |  |
| UL1363 (Power Tap)                | UL1363 (Series Number: AGIB12015SL)  |
| cUL / CSA (Canada)                | cUL (Series Number: AGIB12015SL)   |
| <b>WARRANTY</b>                   |  |
| Product warranty                  | Lifetime   |