



## Model #: SMART1000RM1U

### SmartPro Rackmount UPS - Line interactive, sine wave UPS with integrated switched PDU and current monitoring

#### Highlights

- 1000VA / 1kVA line interactive 1U rackmount UPS
- Maintains sine-wave 120V nominal output over an input range of 83 to 147V
- Network communications supported via USB port, serial port, SNMP/Web card slot and EPO interface
- Current monitoring and switched PDU control via 2 single-outlet load banks
- Input: NEMA 5-15P (120V 15A) / Output: 6 NEMA 5-15R (120V)
- 2 year product warranty .



#### Description

1000VA line interactive UPS for server, network and telecommunications equipment/1U rackmount form factor/Corrects brownouts and overvoltages from 83 to 147/Sine wave output in both AC and battery mode/Uninterruptible Power Supply (UPS) maintains battery derived AC output during blackouts and severe voltage fluctuations/NEMA 5-15P input plug/Network-grade AC surge and noise suppression/Network management interfaces includes USB port, DB9 serial port and SNMPWEBCARD slot/Supports simultaneous detailed monitoring of equipment load levels, self-test data and mains power conditions via all 3 network interfaces at once/Includes PowerAlert monitoring software and complete cabling/Emergency Power Off (EPO) interface/Integrated 2 bank switched PDU/3 stage metered current monitoring and battery charge LEDs/Mains power and voltage regulation LEDs/Audible alarm/Self-test/Supports 2 or 4 post rackmount installation/Field replaceable, hot swappable internal batteries/Attractive all-black UPS design.

#### Applications

Ideal for protection of file servers, network accessories and telecommunications equipment in server rooms, internetworking closets, co-location racks, kiosks and a variety of other locations. Common applications include any mix of servers, workstations, hubs, routers, concentrators, IP telephony and traditional PBX switching systems.

#### Package Includes

- SMART 1000RM1U UPS System
- Mounting hardware
- Cabling for USB & DB9 monitoring and EPO switching
- PowerAlert unattended shutdown and UPS/Power monitoring software
- Warranty information and instruction manual

#### Features

- 1000VA/640 watt output power capacity compatible with North American 120V/60Hz power
- 1U rackmount UPS installs in standard 2 or 4 post 19 inch racks with a depth of only 16.75 inches
- Protects sensitive networking equipment from blackouts, voltage fluctuations and transient surges
- Regulation (AVR) corrects inputs from 83-147VAC back to usable 120V levels without consuming battery power
- Line interactive Automatic Voltage Regulation (AVR) corrects inputs from AVR circuits boost undervoltages by 14% depending on the severity

and reduces overvoltages by 12%

Network interfaces support simultaneous communications via USB, DB9 serial and SNMPWEBCARD slot

Included PowerAlert UPS monitoring software supports safe unattended shutdown, monitoring and control via local connected servers, plus any number of additional servers over IP

Communications ports support on-battery, low-battery, power-restored, AC-voltage, DC-voltage, output current monitoring, battery charge current, battery capacity, internal UPS temperature, AC line frequency, timed inverter shutoff, activate self-test and load bank output power control

Built in Emergency Power Off (EPO) interface with cable

Sine wave output in AC and battery modes

Half load runtime of 15 minutes (500VA/320 watts)/Full load runtime of 7 minutes (1000VA/640 watts)

Includes 6 NEMA 5-15R output receptacles arranged in 2 switchable single-outlet load banks

Integrated 2 bank switched PDU enables remote outlet management for load shedding or remote reboot of individual devices

3 stage metered LEDs offer current monitoring and battery charge level

Mains power and voltage regulation LEDs offer at-a-glance power status information

Front panel switches support self-test and alarm cancel functions

UPS ships fully assembled in full compliance with DOT regulations, no time consuming connection of internal batteries by user required

UL (USA), cUL (Canada), NOM (Mexico), FCC Class A (Emissions) listed

## Specifications

SYSTEM OVERVIEW	
<b>Voltage compatibility</b>	120 VAC
<b>Frequency compatibility</b>	60 Hz
OUTPUT	
<b>Output VA</b>	1000
<b>Output watts</b>	640
<b>Output nominal voltage</b>	120VAC sine wave output in AC and battery mode
<b>Output voltage regulation</b>	LINE MODE: Sine wave line voltage 120V (-21% +8%), BATTERY MODE: Sine wave output within 5% of 120VAC
<b>Output frequency regulation</b>	LINE MODE: Passes line frequency of 60Hz +/-10% BATTERY MODE: Inverter output regulated to 60Hz +/-0.5Hz
<b>Outlet quantity / type</b>	6 NEMA 5-15R
<b>Customized load management receptacles</b>	"Includes 2 load banks, each with 2 outlets that support automated load shedding and remote reboot on demand of locked network devices. Configurable via PowerAlert software to automatically switch off optional loads, like monitors, to increase available runtime for servers and other critical devices. "
<b>Overload protection</b>	Via 15A input breaker
INPUT	
<b>Maximum input amps</b>	9.2A
<b>Input connection type</b>	NEMA 5-15P
<b>Input cord length</b>	10 ft., 14 gauge
<b>Recommended Electrical Service</b>	15A 120V
BATTERY	
<b>Full load runtime</b>	7 minutes (640 watts)
<b>Half load runtime</b>	15 minutes (320 watts)
<b>DC system voltage</b>	24 VDC
<b>Typical battery lifespan</b>	3-6 years, depending on usage

<b>Battery recharge rate</b>	2-4 hours to 90%
<b>Replacement Battery Cartridge</b>	RBC64-1U
<b>VOLTAGE REGULATION</b>	
<b>Voltage regulation description</b>	Line interactive voltage regulation system corrects input voltages between 83 and 147 back to usable 120V nominal levels.
<b>Overvoltage correction</b>	Input voltages between 128 and 147 are reduced by 12%
<b>Brownout correction</b>	Input voltages between 83 and 107 are boosted by 14%
<b>LEDS ALARMS &amp; SWITCHES</b>	
<b>Front panel LEDs</b>	5 front panel LEDs - Green POWER LED, 3 color BATTERY CHARGE LED, 3 color OUTPUT LOAD LEVEL LED, red BATTERY WARNING LED.
<b>Alarms</b>	3 function audible alarm indicates power failure conditions (4 short beeps every 10 seconds), overload (continuous short beeps) and low battery (continuous tone)
<b>Switches</b>	Yes, includes 2 front panel mounted push-button switches for system enable, self-test and alarm cancel functions
<b>SURGE / NOISE SUPPRESSION</b>	
<b>AC surge suppression</b>	480 joules
<b>AC suppression response time</b>	Instantaneous
<b>EMI / RFI AC noise suppression</b>	Yes
<b>PHYSICAL</b>	
<b>Shipping weight (lbs)</b>	36
<b>Shipping weight (kg)</b>	16.3
<b>Shipping Dimensions (HWD/in)</b>	6.25 x 23.5 x 22.5
<b>Shipping Dimensions (HWD/cm)</b>	15.9 x 60 x 57.2
<b>Unit weight (lbs)</b>	32
<b>Unit weight (kg)</b>	14.5
<b>Unit Dimensions (HWD/in)</b>	1.75 x 17.5 x 16.75
<b>Unit Dimensions (HWD/cm)</b>	44.5 x 44.5 x 42.5
<b>Material of construction</b>	Steel
<b>Form factors supported</b>	Rack (1U)
<b>Cooling method</b>	Built-in cooling fan
<b>Battery Access</b>	Battery access door allows hot swap battery replacement without powering connected equipment off
<b>ENVIRONMENTAL</b>	
<b>Operating Temperature</b>	+32 to +104 degrees Fahrenheit / 0 to +40 degrees Celsius
<b>Storage Temperature</b>	+5 to +122 degrees Fahrenheit / -15 to +50 degrees Celsius
<b>Relative Humidity</b>	0 to 95%, non-condensing
<b>Line mode BTU/hr. (Max.)</b>	55.8

<b>Battery mode BTU/hr. (Max.)</b>	189.2
<b>COMMUNICATIONS</b>	
<b>Network monitoring port</b>	Includes 2 built-in monitoring ports, 1-USB & 1-DB9. Each supports on battery, low battery, power restored, AC line voltage, DC battery voltage, load percentage, battery charge current, battery capacity, internal UPS temperature and line frequency status
<b>Software and cabling included</b>	Includes PowerAlert UPS monitoring software for network and standalone operating systems. Ships with complete USB and DB9 cabling.
<b>SNMP compatibility</b>	Built-in accessory slot accommodates internal SNMP / Web card and other network accessories
<b>WatchDog compatibility</b>	Yes, compatible with Tripp Lite's Watchdog system service to restore operation to locked equipment through soft reboot of application / OS or hard power off/on reboot of connected equipment - ideal for unattended kiosk applications
<b>LINE / BATTERY TRANSFER</b>	
<b>Transfer time from line power to battery mode</b>	2-4 milliseconds
<b>Low voltage transfer to battery power</b>	83V (resets to line power as line voltage increases to 87V or higher)
<b>High voltage transfer to battery power</b>	147V (resets to line power as line voltage decreases to 143V or lower)
<b>SPECIAL FEATURES</b>	
<b>EPO port</b>	Includes RJ11 EPO (emergency power off) port and cable
<b>TVSS grounding</b>	Includes back panel grounding point with thumbscrew for data line surge suppressors and other network accessories requiring a safe grounding point
<b>Cold Start</b>	Yes, inverter can be "cold started" to enable temporary AC output during a power failure
<b>Appearance</b>	Attractive black color scheme
<b>CERTIFICATIONS</b>	
<b>Certifications</b>	Tested to UL1778 (USA), cUL (Canada), Class A (emissions), NOM (Mexico)
<b>WARRANTY</b>	
<b>Product warranty</b>	2 year product warranty
<b>Optional coverage</b>	3 year, 5 year, next day and on-site warranty coverage available for select opportunities

## Related Items

<b>Extended Warranties</b>		
WEXT3-500-1500	3-Year Extended Warranty - For Smart Line-Interactive and Online Tower or Rack models, 1500VA or less	Qty: [optional]
WEXT5-500-1500	5-Year Extended Warranty - For Smart Line-Interactive and Online Tower or Rack models, 1500VA or less	Qty: [optional]
<b>Power Distribution</b>		
PS7224	Tripp Lite Power Strip - Multiple outlets wherever you need them	Qty: [optional]
PDU1215	Basic PDU / Power Distribution Unit - Safe, reliable power distribution for critical networking equipment	Qty: [optional]
<b>SNMP Accessories</b>		
ENVIROSENSE	Power Management Tools - Environmental Sensor	Qty: [optional]
SNMPWEBCARD	Power Management Tools - Internal SNMP/Web Card	Qty: [optional]

<b>Surge Protectors</b>		
DTEL2	Network Surge Suppressor - Essential protection for data and communication lines	Qty: [optional]
DNET1	Network Surge Suppressor - Essential protection for data and communication lines	Qty: [optional]
DCATV	Network Surge Suppressor - Essential protection for TV/VCR coaxial lines	Qty: [optional]
<b>USB Hubs/Accessories</b>		
U022-010	USB Cable - 10-ft. USB 2.0 AB Gold Device Cable	Qty: [optional]