Protect It! Surge Suppressor

State of the art protection for every application



Model #: TLP604

- 6 outlets / 4-ft. cord
- 720 joule rating

DESCRIPTION

Tripp Lite's TLP604 offers economical AC surge suppression for protection of workstations, desktop PCs, telecom systems and other sensitive electronics. Built-in AC surge suppression shields connected equipment from damage and performance problems due to transient surges. TLP604 offers 6 total outlets, 4 foot cord and diagnostic LED to warn of suppressor damage. AC suppression rated at 720 joules shields equipment from surges and line noise. Attractive white suppressor housing with keyhole mounting tabs and 1 designated transformer plug outlet offers convenient protection of desktop computer equipment and accessories. Ultimate Lifetime Insurance (USA & Canada Only).

PLUG / OUTLETS: Input: NEMA5-15P / Output: 6 NEMA5-15R / 4-ft. AC line cord

ELECTRICAL: 120V AC, 50/60Hz, 15A (Requires NEMA5-15R wall receptacle)

FORMAT: Corded multi-outlet strip

SUPPRESSION: AC: 150V RMS Clamping / 720 joules / 330V UL1449 Let-through

KEY BUYING POINTS

- 720 joules AC surge suppression shields equipment from the strongest surges and line noise
- 6 AC outlets with room for 1 transformer plug without blocking outlets covers computers and peripherals
- 4 foot AC line cable
- Built-in power switch and 15 amp circuit breaker offers power control and overload protection over all outlets
- Fail-safe thermal fusing protects against fire and other damage in the event of an extreme, extended overvoltage or surge condition
- Diagnostic LED confirms surge suppression status
- Attractive white suppressor housing with keyhole mounting tabs allow versatile placement options
- UL1449 Rated (330V all modes), UL1363 (Power Tap), cUL (Canada)
- Exceeds IEEE 587 category A & B surge suppression specifications
- Lifetime warranty with Itimate Lifetime Insurance (USA & Canada Only)

TYPICAL APPLICATIONS

Ideal for any desktop, network or home computing application requiring AC line protection.

PACKAGE INCLUDES

- TLP604 Surge Suppressor
- · Instruction manual with warranty information

COMPLETE SPECIFICATIONS

| SYSTEM OVERVIEW | |
|------------------------------------|--|
| System overview: | TLP604 surge suppression strip includes 6 AC outlets, 4 foot AC cord, power switch, 720 joule protection level, diagnostic LED, lifetime warranty and connected equipment insurance. |
| Voltage compatibility: | 120 VAC |
| Frequency compatibility: | 50/60 Hz |
| OUTPUT | |
| Output volt amp capacity (amps): | 15 |
| Output watt capacity (watts): | 1800 |
| Outlet quantity / type: | 6 NEMA 5-15R output receptacles |
| Outlet orientation: | Single row |
| Transformer accomodation: | Supports 1 large transformer plug accessory without covering remaining outlets, accepts up to 4 transformers total |
| INPUT | |
| Input connection type: | NEMA 5-15P |
| Input cord length (ft.): | 4 |
| Input cord length (m): | 1.2 |
| Input cord gauge, type: | 14 gauge, SJT |
| Recommended electrical service: | 120V 15A |
| LEDS ALARMS & SWITCHES | |
| Diagnostic LEDs: | Built-in LED confirms suppressor "protection present" (green) status |
| Switches: | Combination AC circuit breaker and 2 position on/off power switch |
| AC SURGE / NOISE SUPPRESSION | |
| Protection modes: | Includes full normal mode (H-N) and common mode (N-G / H-G) line surge suppression |
| AC suppression joule rating: | 720 joules |
| Clamping voltage (RMS): | 150V |
| AC suppression response time: | < 1 ns |
| UL1499 let through rating: | 330V - UL Verified |
| PHYSICAL | |
| Shipping weight (lbs): | 0.8 |
| Shipping weight (kg): | 0.4 |
| Unit weight (lbs): | 0.8 |
| Unit weight (kg): | 0.4 |
| Unit Dimensions (HWD/in): | 1.2 x 10.5 x 1.6 |
| Unit Dimensions (HWD/cm): | 3 x 26.7 x 4.1 |
| Shipping Dimensions (HWD/in): | 1.5 x 12 x 3.75 |
| Shipping Dimensions (HWD/cm): | 3.8 x 30.5 x 9.5 |
| Material of construction: | Plastic |
| Integrated keyhole mounting tabs: | Keyhole mounting tabs enable wall mounting |
| Housing color: | Attractive gray color scheme |
| AC line cord color: | Gray |
| CERTIFICATIONS | |
| UL1449 1998 Rev. (AC Suppression): | UL1449 |
| | |

| UL1363 (Power Tap): | UL1363 |
|--|--|
| cUL / CSA (Canada): | cUL |
| Approvals: | Exceeds IEEE 587 category A&B specifications |
| WARRANTY | |
| Product warranty: | Lifetime |
| Connected equipment insurance (USA and Canada Only): | |

The policy of Tripp Lite is one of continuous improvement.

Specifications are subject to change without notice.

Therefore, your product may vary slightly from what is currently listed.



Tripp Lite World Headquarters 1111 W. 35th Street Chicago, IL 60609 USA

> Customer Support (773) 869-1234

© 2004 Tripp Lite. All Rights Reserved.