

Protect It! Surge Suppressor

State of the art protection for every application



Model #: TLP606

- ▶ 6 outlet / 6-ft. cord
- ▶ 750 joule rating
- ▶

DESCRIPTION

Tripp Lite's TLP606 offers economical AC surge suppression for protection of workstations, desktop PCs, telecom systems and other sensitive electronics. Built-in AC surge suppression shields connected equipment from damage and performance problems due to transient surges. TLP606 offers 6 total outlets, 6 foot cord and diagnostic LED to warn of suppressor damage. AC suppression rated at 750 joules shields equipment from surges and line noise. Attractive white suppressor housing with keyhole mounting tabs offer convenient protection of desktop computer equipment and accessories. Ultimate Lifetime Insurance (USA & Canada Only).

PLUG / OUTLETS: Input: NEMA5-15P / Output: 6 NEMA5-15R / 6-ft. AC line cord

ELECTRICAL: 120V AC, 50/60Hz, 15A (Requires NEMA5-15R wall receptacle)

FORMAT: Corded multi-outlet strip with 1 transformer spaced outlet

SUPPRESSION: AC: 150V RMS Clamping / 750 joules / 330V UL1449

KEY BUYING POINTS

- 6 outlets
- 6-ft. cord
- Surge suppression rating: 750 joules
- EMI/RFI noise filtering
- 15 amp resettable circuit breaker
- Green protection LED
- Includes full normal mode (H-N) and common mode (N-G / H-G) line surge suppression
- Can accommodate 1 large transformer plug without covering remaining outlets, 3 total transformers
- Keyhole support for wall mounting
- Lighted power switch
- Ultimate Lifetime Insurance (USA & Canada only)
- Lifetime product warranty

TYPICAL APPLICATIONS

- Ideal for any desktop, network or home computing application requiring AC line protection

PACKAGE INCLUDES

- TLP606 surge suppressor
- Instruction manual with warranty information

COMPLETE SPECIFICATIONS

| SYSTEM OVERVIEW | |
|------------------------------------|---|
| System overview: | TLP606 surge suppression strip includes 6 AC outlets, 6 foot AC cord, 750 joule protection level, diagnostic LED, lifetime warranty and connected equipment insurance |
| Voltage compatibility: | 120 V AC |
| Frequency compatibility: | 50/60 Hz |
| OUTPUT | |
| Output volt amp capacity (amps): | 15 |
| Output watt capacity (watts): | 1800 |
| Outlet quantity / type: | 6 NEMA 5-15R output receptacles |
| Outlet orientation: | Single row of 6 outlets |
| Transformer accomodation: | Supports 1 large transformer plug accessory without covering remaining outlets, accepts up to 3 transformers total |
| Overload protection: | 15A resettable illuminated combo switch / circuit breaker |
| INPUT | |
| Input connection type: | NEMA 5-15P |
| Input cord length (ft.): | 6 |
| Input cord length (m): | 1.8 |
| Input cord gauge, type: | 14 gauge, SJT |
| Recommended electrical service: | 120V 15A |
| LEDS ALARMS & SWITCHES | |
| Diagnostic LEDs: | Built-in LED confirms suppressor "protection present" (green) status |
| Switches: | Combination AC circuit breaker and 2 position red illuminated on/off power switch |
| AC SURGE / NOISE SUPPRESSION | |
| Protection modes: | Includes full normal mode (H-N) and common mode (N-G / H-G) line surge suppression |
| AC suppression joule rating: | 750 joules |
| Clamping voltage (RMS): | 150V |
| AC suppression response time: | < 1 ns |
| UL1499 let through rating: | 330V - UL Verified |
| PHYSICAL | |
| Shipping weight (lbs): | 1 |
| Shipping weight (kg): | 0.5 |
| Unit weight (lbs): | 0.8 |
| Unit weight (kg): | 0.4 |
| Unit Dimensions (HWD/in): | 10.5 x 1.5 x 1.5 |
| Unit Dimensions (HWD/cm): | 26.7 x 3.8 x 3.8 |
| Shipping Dimensions (HWD/in): | 13 x 4.75 x 1.9 |
| Shipping Dimensions (HWD/cm): | 33 x 12.1 x 4.8 |
| Material of construction: | Plastic |
| Integrated keyhole mounting tabs: | Keyhole mounting tabs enable wall mounting |
| Housing color: | Attractive gray color scheme |
| AC line cord color: | Gray |
| CERTIFICATIONS | |
| UL1449 1998 Rev. (AC Suppression): | UL1449 |
| | |

| | |
|---|--|
| UL1363 (Power Tap): | UL1363 |
| cUL / CSA (Canada): | cUL |
| Approvals: | Exceeds IEEE 587 category A&B specifications |
| WARRANTY | |
| Product warranty: | Lifetime |
| Connected equipment insurance (USA and Canada Only): | |

*The policy of Tripp Lite is one of continuous improvement.
Specifications are subject to change without notice.
Therefore, your product may vary slightly from what is currently listed.*



Tripp Lite World Headquarters
1111 W. 35th Street
Chicago, IL 60609 USA

Customer Support
(773) 869-1234

© 2004 Tripp Lite. All Rights Reserved.