

| Voltage | Switching Freq. (Hz) | Operating Current (mA) | Operating Temp. (°C) | Protection | Housing | Front Cap/Face | Power LED | Output LED | Mating Cord, Cable Length/Jacket | Wiring Diagram # | Wiring Diagrams |
|-----------|----------------------|------------------------|----------------------|------------|---------|----------------|-----------|------------|----------------------------------|------------------|-------------------------|
| 10-65 VDC | 50 | ≤100 | -25 to +70 | IP 67 | Zinc | PA 12 | N/A | YE | 2M/PVC | 1 | <p>Diagram 1</p> |
| 10-30 VDC | 1000 | ≤200 | -30 to +85 | IP 67 | Zinc | PA 12 | GN | YE | 2M/PVC | 2 | <p>Diagram 2</p> |
| | 300 | ≤100 | -25 to +70 | IP 67 | Zinc | PA 12 | GN | YE | 2M/PVC | 2 | |
| | 500 | ≤200 | -25 to +70 | IP 67 | Zinc | PA 12 | GN | YE | 2M/PVC | 2 | |
| | 1000 | ≤200 | -30 to +85 | IP 67 | Zinc | PA 12 | GN | YE | 2M/PVC | 2 | |
| 10-30 VDC | 1000 | ≤200 | -30 to +85 | IP 67 | Zinc | PA 12 | GN | YE | 2M/PVC | 3 | <p>Diagram 3</p> |
| | 300 | ≤100 | -25 to +70 | IP 67 | Zinc | PA 12 | GN | YE | 2M/PVC | 3 | |
| | 500 | ≤200 | -25 to +70 | IP 67 | Zinc | PA 12 | GN | YE | 2M/PVC | 3 | |
| | 1000 | ≤200 | -30 to +85 | IP 67 | Zinc | PA 12 | GN | YE | 2M/PVC | 3 | |
| 10-30 VDC | 1000 | ≤200 | -25 to +70 | IP 67 | Zinc | PA 12 | GN | YE | 2M/PVC | 4 | <p>Diagram 4</p> |
| | 300 | ≤100 | -25 to +70 | IP 67 | Zinc | PA 12 | GN | YE | 2M/PVC | 4 | |
| | 500 | ≤200 | -25 to +70 | IP 67 | Zinc | PA 12 | GN | YE | 2M/PVC | 4 | |
| 10-30 VDC | 1000 | ≤200 | -25 to +70 | IP 67 | Zinc | PA 12 | GN | YE | 2M/PVC | 5 | <p>Diagram 5</p> |
| | 300 | ≤100 | -25 to +70 | IP 67 | Zinc | PA 12 | GN | YE | 2M/PVC | 5 | |
| | 500 | ≤200 | -25 to +70 | IP 67 | Zinc | PA 12 | GN | YE | 2M/PVC | 5 | |
| 5-30 VDC | 1000 | Remote | -25 to +70 | IP 67 | Zinc | PA 12 | N/A | YE | 2M/PVC | 6 | <p>Diagram 6</p> |