

4-Wire *picofast*® Cordsets, Threaded Coupling Nut

- Right Angle Male Connectors
- NEMA 1, 3, 4, 6P and IEC IP 67 Protection
- 125 VAC/VDC, 2 A



Housing Style	Part Number	Cable	Features	Pinout	
	PSW 4M-*	AWM PVC Yellow 4x26 AWG 105° C 4.4 mm OD Cable #RF50697- [†] M [†]	<i>flexlife</i> ®		
	PSW 4M-*/S90	AWM PUR Black 4x26 AWG 105°C 4.4 mm OD Cable #RF50586- [†] M [†]	<i>Cut/Abrasion Immune</i>		
	PSW 4M-*/S90/S101	AWM PUR Black 4x26 AWG 105°C 4.4 mm OD Cable #RF50935- [†] M [†]	<i>Cut/Abrasion Immune, flexlife-10, High flex - over 10 million cycles</i>		1. BN 2. WH 3. BU 4. BK
	PSW 4M-*/S90/S618	AWM PUR Black 4x26 AWG 105°C 4.4 mm OD Cable #RF50602- [†] M [†]	<i>Cut/Abrasion Immune, EMI/RFI Protection</i>		
	PSW 4M-*/S760	AWM PVC Black 4x26 AWG 105°C 4.4 mm OD Cable #RF50870- [†] M [†]	<i>flexlife</i>		
	PSW 4M-*/S90/S653	AWM PUR Black 3x24 AWG 105°C 4.4 mm OD Cable #RF50601- [†] M [†]	<i>Cut/Abrasion Immune, EMI/RFI Protection</i>		1. BN 2. Drain 3. BU 4. BK

* Length in meters. Standard cable lengths are 2, 4, 6, 8 and 10 meters.
 ** Standard coupling material is nickel plated brass.
[†] See Section N for *reelfast*® cable information.