

3-Wire *microfast*® Cordsets, Standard Duty

- Right Angle Male Connectors
- NEMA 1, 3, 4, 6P and IEC IP 67 Protection
- 250 V, 4.0 A



| Housing Style | Part Number    | Cable  | Features   | Pinout |                               |
|---------------|----------------|--|--|--------|-------------------------------|
|               | WSB 3T-*       | AWM PVC Yellow<br>3x22 AWG<br>105°C<br>5.2 mm OD<br>Cable #RF50531- <sup>†</sup> M <sup>†</sup>                    | <i>flexlife</i> ®                                      |        |                               |
|               | WSB 3T-*/S90   | AWM PUR Yellow<br>3x18 AWG<br>80°C<br>5.7 mm OD<br>Cable #RF50547- <sup>†</sup> M <sup>†</sup>                     | <i>Cut/Abrasion Immune</i>                             |        | 1. GN<br>2. RD/BK<br>3. RD/WH |
|               | WSB 3T-*/S105  | AWM PVC Yellow<br>3x22 AWG<br>105°C<br>5.7 mm OD<br>Cable #RF50535- <sup>†</sup> M <sup>†</sup>                    | <i>Braided Copper Shield</i>                           |        |                               |
|               | WSB 3T-*/S749  | AWM PVC Yellow<br>2x22 AWG<br>105°C<br>5.2 mm OD<br>Cable #RF50650- <sup>†</sup> M <sup>†</sup>                    | <i>3-pin with 2 conductors</i>                         |        | 1. N/C<br>2. BK<br>3. WH      |
|               | WSB 3T-*/S1507 | AWM TPE Grey<br>3x20 AWG<br>105°C<br>5.7 mm OD<br>Cable #RF50940- <sup>†</sup> M <sup>†</sup>                      | <i>Flexlife-10, High Flex - Over 10 million cycles</i> |        | 1. BK<br>2. BN<br>3. BU       |
|               | WSB 3T-*/X0R   | AWM PVC Yellow<br>3x18 AWG<br>80°C<br>250°C short term<br>5.7 mm OD<br>Cable #RF04159- <sup>†</sup> M <sup>†</sup> | <i>Weld Flash Immune, High Temp Immune</i>             |        | 1. GN<br>2. RD<br>3. RD/WH    |

\* Length in meters. Standard cable lengths are 2, 4, 6, 8 and 10 meters. Consult factory for other lengths.

\*\* Standard coupling nut material is nickel plated brass "WSB .."; "WSBV .." indicates 316 stainless steel.

<sup>†</sup> See Section N for *reelfast*® cable information.