


8-Wire *euromast*® Cordsets, "C" Style Medium Plug Body

- Right Angle Male Connector
- NEMA 1, 3, 4, 6P and IEC IP 68 Protection
- 60 VAC/75 VDC, 2 A



Housing Style	Part Number	Cable	Features	Pinout
	WSC 8.6T-*	AWM PVC Black 6x24 AWG Foil/Drain 105°C 5.7mm OD Cable #RF50845-*M†	<i>flexlife</i> ®, for <i>picofast</i> 4-port multibox	1. WH 2. GN 3. YE 4. GY 5. BN 6. N/C 7. BU 8. N/C
	WSC 8T-*	AWM PVC Grey 8x24 AWG 105°C 5.7 mm OD Cable #RF50753-*M†	<i>flexlife</i>	
	WSC 8T-*/S715	AWM PVC Yellow 8x24 AWG 105°C 5.7 mm OD Cable #RF50884-*M†		1. WH 2. BN 3. GN 4. YE 5. GY 6. PK 7. BU 8. RD
	WSC 8T-*/S90	AWM PUR Grey 8x24 AWG 105°C 5.7 mm OD Cable #RF50984-*M†	Cut/Abrasion Immune	
	WSC 8T-*/S101	AWM TPE Grey 8x24 AWG 80°C 5.7 mm OD Cable #RF50911-*M†	<i>flexlife-10, High Flex</i> Over 10 Million Cycles	
	WSC 8T-*/S618	AWM PVC Grey 8x24 AWG Foil/Drain 105°C 5.7 mm OD Cable #RF50815-*M†		
	WSC 8T-*/S1555	AWM PVC Black 7x24 AWG Foil/Drain 105°C 6.0 mm OD Cable #RF50761-*M†	RFI/EMI Shielding	1. WH 2. BN 3. GN 4. YE 5. GY 6. PK 7. BU 8. Drain
	RSC 8.8T-*	AWM PVC Grey 8x24 AWG 105°C 5.7 mm OD Cable #RF50753-*M†	<i>flexlife</i>	1. WH 2. GN 3. YE 4. GY 5. BN 6. PK 7. BU 8. RD



\* Length in meters. Standard cable lengths are 2, 4, 6, 8 and 10 meters. Consult factory for other lengths.  
 \*\* Standard coupling nut material is nickel plated brass "WSC .."; "WSCV .." indicates 316 stainless steel.  
 † See Section N for *reelfast*® cable information.