


5-Wire *minifast*® Cordsets, Standard

- Right Angle Male Connectors
- NEMA 1, 3, 4, 6P and IEC IP 67 Protection
- 300 V, 9 A



Housing Style	Part Number	Cable	Features	Pinout
	WSM 50-*M	AWM PVC Yellow 5x18 AWG 105°C 7.3 mm OD Cable #RF50549-*M [†]	<i>flexlife</i> ®	1. BK 2. BU 3. GN/YE 4. BN 5. WH
	WSM 50-*M/S90	AWM PUR Yellow 5x18 AWG 105°C 7.3 mm OD Cable #RF50751-*M [†]	<i>Cut/Abrasion Immune</i>	
	WSM 50-*M/S1551	AWM PVC Yellow 5x18 AWG 105°C 7.3 mm OD Cable #RF50578-*M [†]	<i>Yellow conductor instead of Green/Yellow</i>	1. BK 2. BU 3. YE 4. BN 5. WH
	WSM 511-*M	AWM PVC Yellow 5x18 AWG 105°C 7.3 mm OD Cable #RF50521-*M [†]	<i>flexlife</i>	1. RD/WH 2. RD/BU 3. GN 4. RD/OG 5. RD/BK
	WSM 511-*M/S600	SJOOW CPE Yellow 5x18 AWG 105°C 9.2 mm OD Cable #RF50659-*M [†]	<i>Weld Flash Immune, Flame Immune</i>	



* Length in Meters. Standard cable lengths are 2, 4, 5, 6, 8 and 10 meters. Consult factory for other lengths.
Standard coupling nut material is nickel plated brass "WSM .."; "WS .." indicates nylon and "WSV .." indicates 316 stainless steel.
[†] See Section N for *reelfast*® cable information.

5-Wire *minifast*® Cordsets, Standard

- Straight Female Connectors
- NEMA 1, 3, 4, 6P and IEC IP 67 Protection
- 300 V, 9 A



Housing Style	Part Number	Cable	Features	Pinout
	RKM 50-*M	AWM PVC Yellow 5x18 AWG 105°C 7.3 mm OD Cable #RF50549-*M [†]	<i>flexlife</i> ®	1. BK 2. BU 3. GN/YE 4. BN 5. WH
	RKM 50-*M/S90	AWM PUR Yellow 5x18 AWG 105°C 7.3 mm OD Cable #RF50751-*M [†]	<i>Cut/Abrasion Immune</i>	
	RKM 50-*M/S1551	AWM PVC Yellow 5x18 AWG 105°C 7.3 mm OD Cable #RF50578-*M [†]	<i>Yellow conductor instead of Green/Yellow</i>	
	RKM 511-*M	AWM PVC Yellow 5x18 AWG 105°C 7.3 mm OD Cable #RF50521-*M [†]	<i>flexlife</i>	
	RKM 511-*M/S600	SJOOW CPE Yellow 5x18 AWG 105°C 9.2 mm OD Cable #RF50659-*M [†]	<i>Weld Flash Immune, Flame Immune</i>	

* Length in Meters. Standard cable lengths are 2, 4, 5, 6, 8 and 10 meters. Consult factory for other lengths.
Standard coupling nut material is nickel plated brass "RKM .."; "RK .." indicates nylon and "RKV .." indicates 316 stainless steel.
[†] See Section N for *reelfast*® cable information.