

## 1-1337446-1 Product Details



**1-1337446-1**

TE Internal Number: 1-1337446-

1

 Active

### BNC RF Connectors

 [Converted to EU RoHS/ELV Compliant \(Statement of Compliance\)](#)

#### Product Highlights:

- Connector
- Connector Type = BNC
- Jack
- Body Style = Panel
- Not Surface Mountable

[View all Features](#)

### Documentation & Additional Information

#### Product Drawings:

- [BNC PANEL SOCKET 50 OHM & 75 OHM](#) (PDF, English)

#### Catalog Pages/Data Sheets:

- None Available

#### Product Specifications:

- None Available

#### Application Specifications:

- None Available

#### Instruction Sheets:

- None Available

#### CAD Files:

- None Available

#### Additional Information:

- [Product Line Information](#)

#### Related Products:

- [Tooling](#)

[List all Documents](#)

### Product Features (Please use the Product Drawing for all design activity)

#### Product Type Features:

- [Product Type](#) = Connector
- [Connector Type](#) = BNC
- [Gender](#) = Jack
- Body Style = Panel
- [Grade](#) = Professional
- [Body Material](#) = Brass
- [Sealed](#) = No
- [Isolated](#) = No
- [Dielectric Material](#) = PTFE
- Number of Ports = 1
- Solder Terminal = With

#### Mechanical Attachment:

- Surface Mountable = No
- [Panel Attachment](#) = With
- [Panel Attachment Method](#) = Flange
- Panel Attachment Style = Rear Mount, Front Mount
- Panel Cutout = 1 x 9.0 + 4 x 3.2 Front Mount, 1 x 12.0 + 4 x 3.2 Rear Mount
- Flange Dimension [Sq.] (mm [in]) = 17.50 [0.689]

#### Body Related Features:

- [Hardware Included](#) = No
- [Body Plating](#) = Silver
- [Polarized](#) = No

#### Contact Related Features:

- [Center Contact Material](#) = Brass
- [Center Contact Plating](#) = Silver

#### Industry Standards:

- Government/Industry Qualification = No
- [RoHS/ELV Compliance](#) = RoHS compliant, ELV compliant
- [Lead Free Solder Processes](#) = Wave solder capable to 240°C, Wave solder capable to 260°C, Wave solder capable to 265°C
- RoHS/ELV Compliance History = Converted to comply with RoHS directive

#### Conditions for Usage:

- Operating Temperature (Max.) (°C) = 165

#### Packaging Related Features:

- Packaging Method = Individual
- Packaging Quantity = 50

**Electrical Characteristics:**

- [Connector Impedance \( \$\Omega\$ \)](#) = 75
- Frequency = DC - 2 GHz

**Other:**

- Brand = Greenpar