

1-1478961-0 Product Details



1-1478961-0

TE Internal Number: 1-1478961-0

 **Obsolete**

[Contact Product Information Center](#)

SMA/QMA RF Connectors

 [Converted to EU RoHS/ELV Compliant \(Statement of Compliance\)](#)

Product Highlights:

- Connector - RF
- RF Connector Type = SMA
- Jack
- Terminate To Coaxial Cable
- Without Snap-Lock

[View all Features](#)

Quick Links

- ▶ [Check Pricing & Availability](#)
- ▶ [Search for Tooling](#)
- ▶ [Product Feature Selector](#)
- ▶ [Contact Us About This Product](#)

[Add to My Part List](#)

[Request Sample](#)

[Find Similar Products](#)

[Buy Product](#)

Documentation & Additional Information

Product Drawings:

- None Available

Catalog Pages/Data Sheets:

- None Available

Product Specifications:

- None Available

Application Specifications:

- None Available

Instruction Sheets:

- None Available

CAD Files:

- None Available

Additional Information:

- [Product Line Information](#)

Related Products:

- [Tooling](#)

Product Features (Please use the Product Drawing for all design activity)

Product Type Features:

- [Product Type](#) = Connector - RF
- RF Connector Type = SMA
- [Gender](#) = Jack
- [Crimp Type](#) = Hex
- [Body Style](#) = Bulkhead
- [Number of Panel Mount Holes](#) = 1
- [Body Material](#) = Stainless Steel
- [Body Finish](#) = Gold
- [Center Contact](#) = With
- Grade = Professional
- Panel Thickness (mm [in]) = 3.20 [0.126]
- Dielectric Material = PTFE
- Sealed = No
- Isolated = No
- Flats Dimension = 8.0 A/F

Mechanical Attachment:

- [Panel Attachment](#) = With
- [Panel Attachment Method](#) = Bulkhead
- [Panel Attachment Style](#) = Rear Mount
- Lockwasher Material = Mild Steel
- Lockwasher Plating = Gold
- Nut Material = Stainless Steel
- Panel Cutout = 6.4 x 6.0 D Shape
- Flange Dimensions = 8.0 A/F Hex
- Flange and Thread Material = Stainless Steel

Electrical Characteristics:

- Impedance (Ω) = 50
- Frequency = DC - 18 GHz

Termination Related Features:

- [Coaxial Cable Termination Type](#) = MIL-Crimp

Body Related Features:

- Snap-Lock = Without
- [Length \(mm \[in\]\)](#) = 18.70 [0.736]
- Ferrule Material = Brass
- Ferrule Plating = Gold
- Polarized = No
- Hexcrimp Dimension = 1.75 + 2.6 + 5.6 + 6.5

Contact Related Features:

- Center Contact Material = Beryllium Copper
- Center Contact Plating = Gold

Configuration Related Features:

- [Coaxial Cable Type \(RG/U or Mfg.\)](#) = 142B, 223, 400, 55B, KX 23

Industry Standards:

- Government/Industry Qualification = No
- [RoHS/ELV Compliance](#) = RoHS compliant, ELV compliant
- [Lead Free Solder Processes](#) = Wave solder capable to 240°C, Wave solder capable to 260°C, Wave solder capable to 265°C
- RoHS/ELV Compliance History = Converted to comply with RoHS directive

Conditions for Usage:

- [Terminate To](#) = Coaxial Cable
- Operating Temperature (Max.) (°C) = 165

Packaging Related Features:

- Packaging Quantity = 100

Other:

- Brand = Greenpar