

- [Check Distributor Inventory](#)
- [Find Authorized Distributors](#)

## [My Account](#)

- [Sign In](#)
- [Register](#)


## [Customer Support](#)

- [Support](#)
- [RoHS Support Center](#)
- [Glossary of Terms](#)
- [eBulletin Newsletter](#)

[Home](#) > [Products](#) > [By Type](#) > [PCB Connectors - Wire to Board - Power](#) > [Product Feature Selector](#) > Product Details

# 1-480319-0 Product Details

 **Live Product Chat** US Only  
8:30am - 5pm ET, Mon - Fri



**1-480319-0**

 [Active](#)

 [View 3D PDF](#)

**.200" Centerline, 250 V, 13 A max.**



[Always EU RoHS/ELV Compliant \(Statement of Compliance\)](#)

### Product Highlights:

- Housing
- Contact Diameter = 2.13 mm
- Number of Circuits = 2
- 5.08 mm Centerline, Matrix
- In-Line Contact Layout

[View all Features](#) | [Find Similar Products](#)

Quick Links

- [Check Pricing & Availability](#)
- [Search for Tooling](#)
- [View Mating Products \(4\)](#)
- [View Contacts \(152\)](#)
- [Product Feature Selector](#)
- [Contact Us About This Product](#)

**Documentation & Additional Information**

**Product Drawings:**

- [CAP, 2 CIRCUIT, COMMERCIAL MATE-N-LOK](#) (PDF, English)

**Catalog Pages/Data Sheets:**

- [SOFT SHELL PIN AND SOCKET CONNECTORS](#) (PDF, English)

**Product Specifications:**

- None Available

**Application Specifications:**

- [MATE-N-LOK Commercial Pin And Socket Contacts](#) (PDF, English)
- [MATE-N-LOK Commercial Pin and Socket Contacts](#) (PDF, Japanese)

**Instruction Sheets:**

- [AMP\\* DENTENT-ENGAGEMENT MATE-N-LOK\\* CONNECTORS](#) (PDF, English)
- [Commoning Tabs for MATE-N-LOK Connectors](#) (PDF, English)
- [MATE-N-LOK Contact and Housing Selection Charts](#) (PDF, English)

**CAD Files:** ([CAD Format & Compression Information](#))

- [2D Drawing](#) (DXF, Version N)
- [3D Model](#) (IGES, Version N)
- [3D Model](#) (STEP, Version N)

**Additional Information:**

- [Product Line Information](#)

**Related Products:**

- [Tooling](#)
- [Mating Products \(4\)](#)
- [Contacts \(152\)](#)

[List all Documents](#)

**Product Features (Please use the Product Drawing for all design activity)****Product Type Features:**

- Product Type = Housing
- Number of Circuits = 2
- Mount = Free Hanging
- Color = Natural
- Lock Type = Detent Lock
- Connector Line = Commercial MATE-N-LOK
- Comment = Housing accepts double wire applications where individual insulation diameters do not exceed 2.92 [.115].

**Electrical Characteristics:**

- Voltage (VAC) = 250

**Body Related Features:**

- Contact Diameter (mm [in]) = 2.13 [0.084]
- Centerline, Matrix (mm [in]) = 5.08 [.200]
- Housing Type = Receptacle (Cap)

**Contact Related Features:**

- Contact Layout = In-Line

**Housing Related Features:**

- Housing Material = Nylon
- Housing Flammability Rating = UL 94V-2

**Industry Standards:**

- [RoHS/ELV Compliance](#) = RoHS compliant, ELV compliant
- [Lead Free Solder Processes](#) = Not relevant for lead free process
- RoHS/ELV Compliance History = Always was RoHS compliant

**Packaging Related Features:**

- Packaging Method = One Piece Housing

**Other:**

- Brand = AMP

[Provide Website Feedback](#) | [Contact Customer Support](#)

[Home](#) | [Customer Support](#) | [Suppliers](#) | [Site Map](#) | [Privacy Policy](#) | [Browser Support](#)

© 2008 Tyco Electronics Corporation All Rights Reserved