	Search	Enter Part No.	Go		My Pa	My Parts (0 items) Registe		
Product Name	Cross-Ref Catalog Literature	Industries	Standards	Contact Us	About Us	Investors	Logi Careers	
Connectors	Sockets I/O Connectors	Cable	Fiber Optics	Printed Circui		ation and	And	
<u>.</u>		Assemblies		Products	Ele	ctrical	More	
	Home Crimp Housings Datashee							
tch Language		۲ ۲						
glish 🗧	Part Number: 0022552261	1		Г				
d Accietence 2		-						
d Assistance? act Us	Status: Active Overvie					ø_	\rightarrow	
a Distributor	Description: 2.54mm (.100") Pite Nonpolarized, 26 Circuits	ch SL™ Crimp Ho	ousing, Dual Ro	w, Version A,	5	°° ¢		
er Samples n Library	Documents:					_>_`	/	
	Note - Please disable browser pop	-up blockers for do	ocuments on www	v.molex.com		Š –		
Printer-friendly page	Drawing (PDF)	Product Spe (PDF)	ecification PS-7	<u>0058</u>	1	L.		
Email this page	Product Specification PS-70400			L	Series	image - Referei	nce only	
	(PDF) Related October Page (PDF)	Packaging S	Specification (P		EU RoHS		China Rol-	
	Related Catalog Page (PDF)					HS Compliant		
	Order Products:							
	Check Distributor Inventory	Add to My	Parts					
	Request Samples							
	Part Detail: (show all)				Need more i compliance	nformation or	product	
	General Physical Electric	al Material Info)					
	General			E	Email produ	ctcompliance	@molex.co	
	Product Family	Cr	rimp Housings			Contact Us sectio	n for any non-	
	Series		1450	•		ince questions.		
	Comments		ersion A					
	Overview Product Name	<u>SL</u> SL	TM					
					Search Pa	rts in this Ser	ies	
	Physical				70450 Serie	es		
	Breakaway Circuits (maximum)	No 26						
	Color - Resin		ack		Mates With		7 70500	
	Flammability		IV-0		71308, 713	<u>3, 70029</u> , 7056 [°] 49, <u>70287, 702</u>	7, 70568, <u>27, 70280</u> ,	
	Gender Material - Resin		emale olyester		<u>70260, 8723</u>	<u>3, 8724, 70204</u>		
	Number of Rows	2	.,					
	Packaging Type	Ba	•		Use With	- 4		
	Panel Mount Pitch - Mating Interface (in)	Nc 0.1	o 100 In		<u>70058</u> , <u>718</u>	<u>) </u>		
	Pitch - Mating Interface (mm)		54 mm					
	Stackable Temperature Range - Operating	Ye -4(es 0°C to +105°C					
	Electrical							
	CSA	LF	R19980					
	UL		29179					
	Material Info							
	Old Part Number	70	450-0012					
	Reference - Drawing Numbers	;						
	Product Specification		S-70058					
	Product Specification		S-70400					

$\overline{\}$	13	12	11	10	9	8		7	6	5		4	з	2		1	
			1		1		I					CKT. SIZE	EDP. NO.	ENG. NO.	A	В	
						NOTES:	_					4	022-55-2041	70450-0001	<u>(2.54)</u> .100	<u>(5.05)</u> .199	
							MATERIAL: G.					6	022-55-2061	70450-0002	<u>(5.08)</u> .200	<u>(7.59)</u> .299	L
							PT. NO. 700)58-**** &				8	022-55-2081	70450-0003	<u>(7.62)</u> .300	(10.13) .399	
			-OPTION	"A"-			SEE CHART F TO BE USED		SIZES.	RD. PINS.		10	022-55-2101	70450-0004	<u>(10.16)</u> .400	<u>(12.67)</u> .499	
						5) F		ABLE END	TO END AND SI			12	022-55-2121	70450-0005	<u>(12.70)</u> .500	(15.21) .599	
						6) (REFER TO PH	RODUCT SPE	CIFICATION PS	-70058.		14	022-55-2141	70450-0006	<u>(15.24)</u> .600	<u>(17.75)</u> .699	
			┣━── В −				PACKAGE PEF		-100. SS C OF COSME	TIC		16	022-55-2161	70450-0007	<u>(17.78)</u> .700	<u>(20.29)</u> .799	
			 	٩			SPECIFICATIO					18	022-55-2181	70450-0008	(20.32) 800	(22.83) .899	
н												20	022-55-2201	70450-0009	<u>(22.86)</u> .900	<u>(25.37)</u> .999	ц
												22	022-55-2221	70450-0010	(25.40) 1.000	<u>(27.91)</u> 1.099	
					•							24	022-55-2241	70450-0011	(27.94) I. 100	<u>(30.45)</u> I.199	
												26	022-55-2261	70450-0012	(<u>30.48)</u> 1.200	(32.99) 1.299	
G				Ι								28	022-55-2281	70450-0013	(<u>33.02)</u> 1.300	(35.53) 1.399	G
												30	022-55-2301	70450-0014	<u>(35.56)</u> 1.400	(<u>38.07)</u> 1.499	4
												32	022-55-2321	70450-00 15	(38.10) 1.500	<u>(40.61)</u> 1.599	
												34	022-55-2341	70450-0016	(40.64) 1.600	<u>(43.15)</u> 1.699	
F												36	022-55-2361	70450-0017	<u>(43.18)</u> 1.700	(45.69) 1.799	F
			C 🛥	7								38	022-55-2381	70450-00 18	<u>(45.72)</u> 1.800	(48.23) 1.899	
		CKT. NO. I		₩N		= ¶ f	F					40	022-55-2401	70450-00 19	(48.26) 1.900	(50.77) 1.999	
												42	022-55-2421	70450-0020	(50.80) 2.000	<u>(53.31)</u> 2.099	
E				48			24)					44	022-55-2441	70450-0021	(53.34) 2.100	(55.85) 2.199	Е
				10			24) 00 REF.					46	022-55-2461	70450-0022	(55.88) 2.200	(58.39) 2.299	
											-	48	022-55-2481	70450-0023	<u>(58.42)</u> 2.300	(60.93) 2.399	
			XW X								-	50	022-55-2501	70450-0024	(60.96) 2.400	(63.47) 2.499	
D					N 17	N	L				-	52	022-55-2521	70450-0025	(63.50) 2.500	(66.01) 2.599	D
			C 🔫								L	54	022-55-2541	70450-0026	<u>(66.04)</u> 2.600	<u>(68.55)</u> 2.699	
					SECTION	N C-C											
с																	С
																	<u> </u>
						Г	~~~~				DIMENSION	STYLE	SCALE	DESIGN UNITS			
в							PEC	QUALITY SYMBOLS	GENERAL TOL	CIFIED)	MM/	IN	4:1) ANGLE ECTION	В
							2009 2009	₹ ▼=0 4	PLACES ±	± MJM		DATE 1986/10		OUSING - CO			
							ADD COSMETIC SPEC EC NO: UCP2007-2009 DRWN:DMRGAN 2007/02/13 CHYCD:MSIBARRA 2007/02/13 APPR:SMILLER 2007/02/13		PLACES ± PLACES ± 0.25	±.014 MJM		DATE 1986/10)UAL ROW (GRID STAC		U I	<u> </u>
							OSP UCP2 10RGA 31BAR		1 PLACE ± 0.35 ANGULAF	± APP	ROVED BY	DATE 1986/10		OLEX INCO		FED	
A							NO			МАТ	- Erial no. SEE CH		DOCUMENT NO.	0450-0001-0	1026	SHEET NO. 1 OF 1	A
						F			RAFT WHERE , MUST RE WITHIN DIME	MAIN SIZ	E THIS DR	awing c	ONTAINS INFORMA	TION THAT IS PR	ROPRIETARY	TO MOLEX	
/tb.	_frame_C_P_ME	12	11	10	9	8		7	6	5		ATED A	ND SHOULD NOT	BE USED WITHOU		PERMISSION	
Re	₹v. E 2006/04/1	15 12			,	U		,	0	د		-	د	2	I		$\overline{\}$