



## 1337815-1 Product Details

<p>No Image Available</p>	<p><b>RF Coax Cable Assemblies</b></p> <p> <a href="#">Converted to EU RoHS/ELV Compliant</a> (<a href="#">Statement of Compliance</a>)</p>	
<p><b>1337815-1</b></p> <p>TE Internal Number: 1337815-1  <a href="#">Active</a></p>	<p><b>Product Highlights:</b></p> <ul style="list-style-type: none"> <li>• 2 Connectorized Ends</li> <li>• RF Coax Cable Assemblies Application</li> <li>• Connector Type = SMB Straight Plug to SMB Straight Plug</li> <li>• Assembly Length = .25 M</li> <li>• Coaxial Cable Type (RG/U or Mfg.) = 174</li> </ul>	
<p><b>Documentation &amp; Additional Information</b></p>		
<p><b>Product Drawings:</b></p> <ul style="list-style-type: none"> <li>• None Available</li> </ul> <p><b>Catalog Pages/Data Sheets:</b></p> <ul style="list-style-type: none"> <li>• None Available</li> </ul> <p><b>Product Specifications:</b></p> <ul style="list-style-type: none"> <li>• None Available</li> </ul> <p><b>Application Specifications:</b></p> <ul style="list-style-type: none"> <li>• None Available</li> </ul> <p><b>Instruction Sheets:</b></p> <ul style="list-style-type: none"> <li>• None Available</li> </ul> <p><b>CAD Files:</b></p> <ul style="list-style-type: none"> <li>• None Available</li> </ul>	<p><b>Additional Information:</b></p> <ul style="list-style-type: none"> <li>• <a href="#">Product Line Information</a></li> </ul> <p><b>Related Products:</b></p> <ul style="list-style-type: none"> <li>• <a href="#">Tooling</a></li> </ul>	
<p><b>Product Features (Please use the Product Drawing for all design activity)</b></p>		
<p><b>Product Type Features:</b></p> <ul style="list-style-type: none"> <li>• <a href="#">Connector Type</a> = SMB Straight Plug to SMB Straight Plug</li> </ul> <p><b>Electrical Characteristics:</b></p> <ul style="list-style-type: none"> <li>• Connector Impedance (<math>\Omega</math>) = 50</li> </ul> <p><b>Body Related Features:</b></p> <ul style="list-style-type: none"> <li>• <a href="#">Number of Connectorized Ends</a> = 2</li> <li>• <a href="#">Assembly Length (M [ft])</a> = 0.25 [0.820]</li> <li>• <a href="#">Body Plating</a> = Gold</li> </ul> <p><b>Contact Related Features:</b></p> <ul style="list-style-type: none"> <li>• Center Contact Plating = Gold</li> </ul>	<p><b>Configuration Related Features:</b></p> <ul style="list-style-type: none"> <li>• <a href="#">Coaxial Cable Type (RG/U or Mfg.)</a> = 174</li> </ul> <p><b>Industry Standards:</b></p> <ul style="list-style-type: none"> <li>• <a href="#">RoHS/ELV Compliance</a> = RoHS compliant, ELV compliant</li> <li>• <a href="#">Lead Free Solder Processes</a> = Not relevant for lead free process</li> <li>• RoHS/ELV Compliance History = Converted to comply with RoHS directive</li> </ul> <p><b>Operation/Application:</b></p> <ul style="list-style-type: none"> <li>• Application = RF Coax Cable Assemblies</li> </ul> <p><b>Other:</b></p> <ul style="list-style-type: none"> <li>• Brand = Greenpar</li> </ul>	