

a vital part of your world

Text Search:

Friday, 25 November, 2005

CATALOG

Cross Reference

- [Competitive Products](#)
- [Military Spec P/Ns](#)
- [Tyco Brand P/Ns](#)

Part Number Search

- [Document Search](#)
- [Product Type Search](#)
- [Product Family Search](#)
- [Alphabetical Search](#)
- [RoHS/ELV Compliance & Alternates](#)
- [CAD Model Search](#)
- [Brand Search](#)
- [Tool Search](#)
- [Multiple Part Comparison](#)
- [Lead Free Solutions](#)
- [Help/Glossary](#)

Home

e-bulletin newsletter
SUBSCRIBE NOW!
 click here

Subminiature and Microminiature D Connectors

↳ Standard Cable Connectors

AMP 1571652-3 Active

Not ELV or RoHS Compliant

(Corporate P/N: 1571652-3)

[Search for Compliant \(RoHS/ELV\) Alternates](#)

[Search for Parts](#)

Document links for this part cannot be displayed. Your browser does not support inline frames or is currently configured not to display inline frames. Inline frames are supported in both Internet Explorer 5 and Netscape 6, as well as all later versions of these browsers.

Related Part Information		
General Information	eCommerce	Related Part Information
<ul style="list-style-type: none"> ➤ General Info ➤ Sales Info ➤ Assembly Subcontractors 	<ul style="list-style-type: none"> ➤ Pricing & Availability 	<ul style="list-style-type: none"> ➤ Tooling

Photos & Line Drawings - The photographs and/or line drawings are representative images of a product for viewing purposes only.

[Product Photo](#)

Searchable Features:	
Brand:	AMP
RoHS/ELV Compliance:	Not ELV/RoHS compliant
Lead Free Solder Processes:	Wave solder capable to 240° C
Product Type:	Connector Kit
Product Series:	HD-20 (Solder Cup)
Number of Positions:	25
Shielded:	Yes
Gender:	Plug
Contacts:	With
Wire/Cable Type:	Round Jacketed Cable
Wire Termination Type:	Solder
Wire Range (mm² [AWG]):	0.5 - 0.6 [20]
Mating Connector Lock:	With
Mating Connector Lock Type:	Jackscrews
Pre-Assembled:	No
Shell Size:	3
Shell Type:	Full Metal Shell
Contact Mating Area Plating:	Gold Flash

Other Properties:	
Contact Material:	Brass
Enclosure Material:	PVC
Jackscrew Material:	Brass
Color:	Black
Contact Type:	Solder Cup
Shell Material:	Steel
Shell Plating:	Tin
Shield Material:	Steel
Shield Plating:	Tin
Insert Material:	PBT
Insert Flammability Rating:	UL 94V-0

<u>Contact Termination Area Plating:</u>	Tin-Lead
<u>Contact Size:</u>	20
<u>Cable Insulation Diameter (mm [in]):</u>	10.80 [0.425]
<u>Grounding Indents:</u>	With
<u>Grade:</u>	Standard
<u>Packaging Method:</u>	Bulk

[Copyright and Privacy Statement](#)
Visit [Tyco International Ltd.](#)

[[Products](#) | [Catalog](#) | [Brands](#) | [Industries](#) | [Commerce](#) | [Supplier](#) | [Contact Us](#) | [About](#) | [Home](#)]