

- [Check Distributor Inventory](#)
- [Find Authorized Distributors](#)

. My Account

- [Sign In](#)
- [Register](#)


. Customer Support

- [Support](#)
- [RoHS Support Center](#)
- [Glossary of Terms](#)
- [eBulletin Newsletter](#)

[Home](#) > [Products](#) > [By Type](#) > [Product Feature Selector](#) > Product Details

2-520182-2 Product Details

 **Live Product Chat** US Only
8:30am - 5pm ET, Mon - Fri



2-520182-2

 [Active](#)

 [View 3D PDF](#)

Ultra-Fast Receptacles & Tabs



[Always EU RoHS/ELV Compliant \(Statement of Compliance\)](#)

Product Highlights:

- Receptacle
- Proprietary Name = Ultra-Fast
- Receptacle Style = Straight
- Tab Fit = 4.75 x 0.51 mm
- Brass Material

[View all Features](#) | [Find Similar Products](#)

Quick Links

- [Check Pricing & Availability](#)
- [Search for Tooling](#)
- [Product Feature Selector](#)
- [Contact Us About This Product](#)

Documentation & Additional Information

Product Drawings:

- [RECEPTACLE ASSY,ULTRA-FAST](#), (PDF, English)

Catalog Pages/Data Sheets:

- [Automachine and General Products](#) (PDF, English)
- [FASTON TERMINALS \(INSULATED & UNINSULATED\)](#) (PDF, English)
- [Ultra-Fast and Ultra Fast Plus](#) (PDF, English)

Product Specifications:

- [Ultra-Fast Fully Insulated FASTON Receptacle Terminals](#) (PDF, English)

Application Specifications:

- [Ultra-Fast Series 110, 125, 187, 205, and 250 Fully-...](#) (PDF, English)

Instruction Sheets:

- None Available

CAD Files: ([CAD Format & Compression Information](#))

- [2D Drawing](#) (DXF, Version M)
- [3D Model](#) (IGES, Version M)
- [3D Model](#) (STEP, Version M)

Additional Information:

- [Product Line Information](#)

Related Products:

- [Tooling](#)

[List all Documents](#)

Product Features (Please use the Product Drawing for all design activity)**Product Type Features:**

- [Product Type](#) = Receptacle
- [Proprietary Name](#) = Ultra-Fast
- [Receptacle Style](#) = Straight
- [Tab Fit \(mm \[in\]\)](#) = 4.75 x 0.51 [.187 x .020]
- [Material](#) = Brass
- [Insulation Diameter \(mm \[in\]\)](#) = 3.43 [.135] Max.
- [Insulation Support](#) = Non-Insulation Support
- Industry Application = Standard
- Finish = Tin

Body Related Features:

- [Wire Range \(mm \[AWG\]\)](#) = 0.30-0.90² [22-18]
- Fully Insulated = Yes
- Flammability Rating = UL 94V-2

Industry Standards:

- [RoHS/ELV Compliance](#) = RoHS compliant, ELV compliant
- [Lead Free Solder Processes](#) = Not relevant for lead free process
- RoHS/ELV Compliance History = Always was RoHS compliant

Packaging Related Features:

- [Packaging Method](#) = Loose Piece

Other:

- Brand = AMP

[Provide Website Feedback](#) | [Contact Customer Support](#)

[Home](#) | [Customer Support](#) | [Suppliers](#) | [Site Map](#) | [Privacy Policy](#) | [Browser Support](#)

© 2008 Tyco Electronics Corporation All Rights Reserved