

201568-1 Product Details



201568-1

TE Internal Number: 201568-1

 [Active](#)

Multimate

 [Always EU RoHS/ELV Compliant \(Statement of Compliance\)](#)

Product Highlights:

- Socket
- Gold (30) over Nickel (50) Contact Mating Area Plating Material
- Wire Range = 2.00-2.15² [14] mm [AWG]
- Brass Contact Base Material
- Type II

[View all Features](#)

Documentation & Additional Information

Product Drawings:

- [CONTACT ASSEMBLY, SOCKT, #16, 14 AWG, TYPE II](#) (PDF, English)

Catalog Pages/Data Sheets:

- [AEROSPACE & DEFENSE](#) (PDF, English)
- [PRECISION PIN AND SOCKET CONTACTS](#) (PDF, English)
- [Signal Contacts](#) (PDF, English)
- [M_SERIES_PIN_AND_SOCKET_CONNECTORS](#) (PDF, English)
- [CIRCULAR CONNECTORS FOR COMMERCIAL SIGNAL AND POWER ...](#) (PDF, English)
- [AMP Circular Connectors for Commercial Signal & Powe...](#) (PDF, English)

Product Specifications:

- [Contact, Type II, Screw Machine](#) (PDF, English)

Application Specifications:

- [Type II Screw Machine Contact](#) (PDF, English)
- [Type Ii Screw Machine Contacts](#) (PDF, English)

Instruction Sheets:

- [Selection Charts for Multimate Pin and Socket Contacts](#) (PDF, English)
- [Application and Maintenance for Hand Crimping Tool \(1\)](#) (PDF, English)
- [Application and Maintenance for Crimping Die Assemblies](#) (PDF, English)
- [Application and Maintenance for Crimping Dies](#) (PDF, English)
- [Application and Maintenance for Hand Crimping Tool \(2\)](#) (PDF, English)

CAD Files: ([CAD Format & Compression Information](#))

- [2D Drawing](#) (DXF, Version U)
- [3D Model](#) (IGES, Version U)
- [3D Model](#) (STEP, Version U)

[List all Documents](#)

Additional Information:

- [Product Line Information](#)

Related Products:

- [Tooling](#)

Product Features (Please use the Product Drawing for all design activity)

Product Type Features:

- [Pin/Socket](#) = Socket
- Product Type = Type II
- [Insulation Support](#) = No
- [Wire Termination Type](#) = Crimp
- Wire/Cable Type = Discrete Wire
- Color Code = Violet/Blue
- Grade = Commercial
- Retention Spring Material = Stainless Steel
- Comment = Use turret TH501 (p/n 1-601967-5) with hand tool 601967-1.; Extraction Tool No. 305183; Insertion Tool No. 200893-2 (for insulation diameters 1.78 [.070] or less).

Mechanical Attachment:

- Contact Retention in Housing = Crimp Snap-In

Electrical Characteristics:

- High Current = No

Body Related Features:

- [Wire Range \(mm \[AWG\]\)](#) = 2.00-2.15² [14]
- Used With = G Series Connectors, M Series Connectors, CPC Connectors

Contact Related Features:

- [Contact Mating Area Plating Material](#) = Gold (30) over Nickel (50)
- [Contact Base Material](#) = Brass
- [Contact Size](#) = 16
- [Contact Type](#) = Signal

Industry Standards:

- [RoHS/ELV Compliance](#) = RoHS compliant, ELV compliant
- [Lead Free Solder Processes](#) = Not relevant for lead free process
- RoHS/ELV Compliance History = Always was RoHS compliant

Conditions for Usage:

- [Terminate To](#) = Wire
- Test Current (Amps.) = 13.0

Packaging Related Features:

- [Packaging Method](#) = Loose Piece

Other:

- Brand = AMP